

# DIGITUS® Adaptador/conversor DisplayPort ativo, DP para HDMI

DB-340415-002-S

EAN 4016032468752



**Cabo adaptador DisplayPort, tipo DP - HDMI A St/Bu,0,2m,c/ bloqueio,UHD 4K,HDMI 2.0,act,gold,sw**

O adaptador/conversor DisplayPort 4K para HDMI (ficha DisplayPort para tomada HDMI) permite-lhe reproduzir conteúdos do seu computador ou portátil diretamente no seu televisor ou noutros ecrãs HDMI. Suporta uma resolução UHD de até 4096 x 2160p. Isto significa que as suas imagens, vídeos, documentos, apresentações, etc. podem ser apresentados em Ultra HD e são ideais para utilização em reuniões ou em casa.

**Converte sinais DisplayPort em sinais HDMI em resoluções até UHD 4K**

**Attributes**

- AWG: 32
- Color cable: black

- Connector 1: DP, plug
- Connector 2: HDMI type A, jack
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.2
- Ferrite filter: none
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Resolution max.: 4096 x 2160 Pixel, 30Hz
- Length: 0.2 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

**Package contents**

- 1 x Adaptador/conversor DisplayPort ativo, DP para HDMI

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	80	7.70	52.00	29.00	39.00	58,812.00
Packaging Unit Inside	20	1.93	27.00	25.00	17.00	11,475.00
Packaging Unit Single	1	0.10	23.50	7.50	2.30	405.38
Net single without Packaging	1	0.09	2.50	4.50	1.50	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)