

DIGITUS Fast Ethernet PoE Switch 4-port PoE + 1-port uplink, 60W PoE Budget

DN-95320-1
EAN 4016032478690



Digitus 4+1 P FE POE Switch 4 x 10/100/1000 RJ 45 Port

The DIGITUS DN-95320-1 is a 5-Port 10/100M Desktop PoE Switch, that enables a seamless network connection. It integrates 100 Mbps Fast Ethernet and 10 Mbps Ethernet network capabilities. These PoE ports can automatically detect IEEE 802.3af/at-compliant Powered Devices (PDs) and supply them with power. The operating mode can be changed using the slide switch on the front side. When switching into extend mode, Ports 2-5 can be switched into long range mode at up to 250 meters with 10 Mbps. The DN-95320-1 is easy to install and to use. It does not require any configuration or installation. With its desktop design, outstanding performance and quality, the 5-Port 10/100 Desktop PoE Switch is an excellent choice for extending video monitoring or WLAN access points.

5-Port 10/100 MBit/s Desktop Switch with four Power over Ethernet ports and an additional uplink port, offers your network considerable improvement in terms of performance and efficiency

- Compatible with the network standards: IEEE 802.3i, IEEE 802.3u, IEEE802.3x, IEEE802.3az
- Supports the standards: IEEE802.3af, IEEE802.3at (up to 30 W per port)
- Standard/extended mode (PoE port rate of 10 Mbps, the farthest distance is 250 m)
- Supports 5 x 10/100Mbps auto-negotiation Fast Ethernet, 4 Port PoE function (Port 2-5)
- Supports IEEE802.3x flow control for full-duplex mode and backpressure for half-duplex mode
- Supports 6KV surge protection for all UTP ports
- LED displays: PoE, link, activity

- External power supply, sophisticated design, suitable for desktop installation
- Transfer method: Store and forward
- Backplane bandwidth: 1 Gbps
- MAC addresses: 1K
- PoE plug configuration: 4/5(+), 7/8(-)
- PoE budget: 60W
- Forwarding rate: 0.744 Mpps per port
- Power consumption: 66.5W max. (PoE Mode)
- Operating temperature: 0 °C to +40 °C
- Operating humidity: 10% - 90% RH (non-condensing)
- Storage temperature: -40 °C to +70 °C
- Storage humidity: 5% to 90% RH (non-condensing)
- Fanless design
- Power adapter data: 53.5 V, 1.2A, external power adapter
- Dimensions: W 140 x D 76 x H 28 mm
- Weight: 609 g (incl. charger)

Attributes

- Industrial usage: no
- Managed: no
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vandalism: no
- VLAN: no

Package contents

- 5-Port 10/100Mbps Ethernet Unmanaged PoE Switch (4-Port PoE)
- 1x installation components
- 1x DC power adapter
- 1 x user manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	16.58	33.00	62.30	47.80	98,272.00
Packaging Unit Inside	1	0.83	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.83	23.00	31.20	5.90	4,233.84
Net single without Packaging	1	0.00	8.20	8.90	2.10	0.00

More images:



Safety notes

- This product is intended for indoor use only.
- Read all instructions and follow all warnings and instructions on the device.
- Do not place this appliance on an unstable surface (such as a trolley, stand, table, etc.).
- Do not use this appliance near water.
- Do not place this appliance near or above a radiator.
- The housing is equipped with openings for heat dissipation and ventilation. To prevent overheating during operation, the ventilation openings must not be blocked or covered.
- Do not place the appliance on a soft surface (e.g. bed, sofa, blanket, etc.). This will block the ventilation.
- The appliance must not be installed in a closed environment if adequate ventilation is not guaranteed.
- Do not spray any liquids onto the appliance.
- Disconnect the mains plug before cleaning. Do not use any liquid or foam cleaners.
- Clean the appliance with a damp cloth.
- Connect the device according to the power supply on the rating plate.
- To prevent damage to the appliance, it is important that all appliances are properly earthed.
- Do not place any objects on the power cable and lay it in such a way as to avoid tripping hazards.
- Use a surge protector, a regulator or an uninterruptible power supply (UPS) to protect your system from sudden, temporary and reduced power.
- Secure the system cable and mains cable properly and ensure that no objects are pressing on the cable.
- Do not insert any objects into the appliance through the openings in the housing. There is a risk of a short circuit, which can lead to fire or electric shock.
- Do not attempt to repair the appliance yourself. Always contact an authorized customer service centre.
- If any of the following conditions occur, unplug the appliance and send it to an authorized service centre for repair
 - The mains cable, power supply unit or plug for the power supply is damaged or worn;
 - Liquid has penetrated the appliance;
 - The device has been exposed to rain or water;
 - The device has been dropped or the housing has been damaged;
 - The function of the device has obviously changed;
- The appliance cannot be operated as described in the operating instructions.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com