DIGITUS® Smart Full HD PT Indoor Camera with Auto-Tracking, WLAN + Voice Control

DN-18603

EAN 4016032478867



Smart Wifi Camera(Without Lan port) P/T Indoor

The WLAN Camera from DIGITUS® can be rotated by 355° and swiveled by 90°, and is equipped with auto tracking to enable automatic tracking of movements within the visual field. Thanks to the wide angle lens of 100° in razor-sharp Full HD resolution, you won't miss a single detail. Automatic day / night vision switching offers a clear view even in absolute darkness. WLAN operation means that you are 100% flexible when it comes to the installation location, simply position the camera within range of your wireless network and ensure the power supply. Using voice control with Amazon Alexa and Google Assistant you can show the camera image on compliant Amazon and Google displays. The camera is also able to recognize and track movement in the image area and send an appropriate push notification to your smartphone. The available microSD card slot can be used for cards up to 128 GB, so that recordings can be stored for longer periods and retrieved at any time. Thanks to two-way audio transmission, you can communicate with people in front of the camera. The live image from the camera and all settings can be easily viewed and set using the app, regardless of your location (mobile reception required). The camera is designed for a variety of applications, for example monitoring interior spaces of all kinds, baby monitoring or pet monitoring. Thanks to the bracket included in delivery, the camera can be individually aligned and attached - alternatively using the integrated 1/4" screw thread. Focus on safety and flexibility with the voice operated Full HD PT indoor camera from DIGITUS®.

Auto-tracking, rotating and pivoting (PT), WLAN, two-way audio, compatible with Amazon Alexa & Google Assistant

- Video resolution: 1920 x 1080p@25 BpS (Full HD)
- Video compression: H.264
- Bit rates: 16 Kbps - 2 Mbps
- Lens: FOV: 100° viewing angle / 3.6 mm lens
- Rotatable by 355° (PAN) / Swivel range 90° (TILT)
- Supports motion detection with auto tracking (movement tracking)
- Light sensitivity: 0.1 Lux / Aperture: F1.2
- Sensor: 1/2.7" CMOS - 2 megapixel
- Night vision range: Up to 5 m
- Day / night switching: IR-CUT (automatic white balancing)
- Video frame rate: Mainstream 1080p@25bps, 720p@25bps
- Infrared LEDs: 6 pcs.
- Integrated speaker and microphone
- Two-way audio communication / compression: G.711
- Wireless LAN: 2.4 GHz (IEEE 802.11b/g/n)
- Recording modes: Manual / Motion / Scheduled
- With microSD card slot
- MicroSD card storage capacity: Up to 128 GB
- Supports cloud storage
- Network protocol: TCP/IP, UDP, DDNS, P2P, RTSP, Private Cloud, ONVIF
- System requirements: iOS 7 / Android 4 or higher
- Security: User authentication, software encryption
- Power supply camera: USB 5 V DC / 1.5 A via MicroSD jack
- Power consumption: 2 - 4 W max.
- Power adapter input voltage: 100 - 240 V, 50/60 Hz, 0.35 A via Euro plug Type C (CEE 7/16)
- Power adapter output voltage: 5 V DC, 1.5 A, 7.5 W via coaxial plug 5.5 mm
- Integrated 1/4" screw thread for optional mounting options
- Adapter for wall and ceiling mounting included
- Operating temperature: -10°C ~ +50°C
- Dimensions: L 85 x W 67 x H 105 mm
- Material: Plastic
- Weight: 280 g incl. bracket
- Color: White

Package contents

- 1 x Smart Full HD PT Indoor Camera with Auto-Tracking, WLAN + Voice Control
- 1 x USB power adapter incl. USB cable x 1m
- 1 x Mounting adapter / mounting material
- 1 x Quick installation guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	50	17.00	29.50	63.00	47.00	87,349.50
Packaging Unit Inside	1	0.34	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.34	11.80	13.80	8.80	1,432.99
Net single without Packaging	1	0.28	8.50	6.70	10.50	0.00

More images:



























EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com