

DIGITUS 24-Port Gigabit PoE Networkswitch, 19 Zoll, unmanaged, 2 Uplink Ports, SFP, 370 W, af/at

DN-95348-1

EAN 4016032480860



24-Port Gigabit + 2-Port Gigabit SFP Multi-Mode Unmanaged PoE Switch

"The DIGITUS 24-Port Gigabit Rack mount Switch with 24 Power over Ethernet ports and two additional SFP Fiber Port, offers your network significant improvement in terms of performance and efficiency. Thanks to PoE support, you only need a single (network) cable for power and data transfer. This switch makes it much easier to connect devices such as access points, network cameras, and IP telephones, and requires far less cabling than alternatives. It also allows you to extend your network in places where there are no power supply cables or sockets available. The switch does not require any configuration and therefore guarantees quick and seamless integration into the network. Moreover, can be manually switched to a Normal mode, or Flow Control mode, or VLAN mode to suitable for various occasions flexibly. Based on Gigabit Ethernet Technology, it is essential to helping solve network bottlenecks that frequently develop as more advanced computer users and newer applications continue to demand greater network resources."

Thanks to the PoE function, no additional power supply unit is required for the connected devices. Minimize cabling for wireless APs, IP telephones, and any other PoE capable device

- Comply with IEEE 802.3i, IEEE 802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.3az standards
- Support IEEE802.3af, IEEE802.3at standards
- Supporting Normal mode, VLAN mode and Extend mode, flexible to switch
- The maximum output power of a single port is 30W, and the total output power of PoE is 370W
- Flow control method: Full-duplex adopts IEEE 802.3x standard, half-duplex adopts Backpressure standard
- Support MAC address self-learning
- 24 x 10/100 / 1000Mbps self-adaptive RJ45 ports, support port auto flip (Auto MDI / MDIX)
- 2 x 1000Mbps optical fiber adaptive ports

- Use store-and-forward architecture
- Backplane: 52Gbps
- Packet forwarding rate: 38.688Mbps
- Packet Cache: 4.1Mbit
- Mac address table: 8K
- Jumbo frame: 9216 bytes
- LED indicators for monitoring power, link/activity
- Working Mode-Normal mode: Enable Flow Control and all ports can communicate with each other.
- Working Mode-Flow Control mode: Disable Flow Control and all ports can communicate with each other.
- Working Mode-VLAN mode: Port 1-24 cannot communicate with each other, but can communicate with the uplink port 25F-26F.
- Working Mode-VLAN mode: Port 1-24 cannot communicate with each other, but can communicate with the uplink port 25F-26F.
- Power supply: AC 100-240V 50 / 60Hz Built-in power
- Power consumption: Max (full load on the port): 400W (220V / 50Hz)
- Dimensions: 440 * 240 * 44mm
- Number of ports: 24
- PoE Power budget: 30 W
- PoE standard: IEEE802.3at (PoE+)
- Ethernet speed: Gigabit
- Industrial usage: no
- Managed: no
- Number of ports (Uplink): 2
- Outdoorsuitable: no
- PoE (Power over Ethernet): yes
- Protection against vanadism: no
- VLAN: no

Package contents

- Gigabit Ethernet PoE Switch 24-port PoE + 2-port SFP, 370W PoE budget
- Power cord
- QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	3	12.25	28.50	57.50	32.50	53,259.40
Packaging Unit Inside	1	4.08	0.00	0.00	0.00	0.00
Packaging Unit Single	1	4.08	29.50	55.50	8.80	14,407.80
Net single without Packaging	1	2.82	20.80	44.00	4.40	0.00

More images:

