

DIGITUS DIGITUS QSFP28 100G 5m DAC cable

DN-81605**EAN 4016032481126****100G QSFP28 Direct Attach Cable Up to 28.3125Gbps data rate per channel 5m**

The Digitus® QSFP28 100G DAC cables are the ideal connection between switches in the backbone area. The 100G QSFP28 to QSFP28 Direct Attach Cable copper cable assemblies(DAC) are a low cost alternative for short reach applications. It is compliant with 100G Ethernet (100GBASE-CR4) specifications. It contains four high-speed copper pairs, each operating at data rates of up to 25GbE. So the QSFP28 DAC cable assembly is suitable for power-efficient connectivity for short distance interconnects, such as Data center, enterprise storage systems and High-Performance Computing.

100G QSFP28 DAC Cable 5m, AWG 26

- Transmission cable length: 5m
- Maximum aggregate data rate: 100Gb/s (4 x 25Gb/s)
- Channel data rates : 28.3125Gbps
- Compliant with the SFF-8665 specifications

- Single +3.3V power supply
- Wire AWG : 26
- Type: Passive / Copper
- End A =QSFP28 4X (SFF 8665)
- End B = QSFP28 4X (SFF 8665)
- Temperature Range : Operating: -0°C to +70°C
- Storage Temperature : -40 to + 85°C
- Compatible switch: CISCO, 3COM, D-LINK, ENTERASYS, EXTREME, FINISAR, FORCE 10, HUAWEI, IBM, JUNIPER, LINKSYS, NETGEAR, NORTEL, RIVERSTONE, ZTE, ZYXEL Allnet
Dell, D-Link, Edimax, Etherwan, Fortinet ...etc

Attributes

- DDM Support: no

Package contents

- QSFP28 100G DAC cable 5m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	60	1.50	48.00	48.00	38.00	87,552.00
Packaging Unit Inside	1	0.03	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.03	26.00	26.00	3.00	2,028.00
Net single without Packaging	1	0.36	5.80	1.40	1.50	0.00

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com