DIGITUS® USB-C - USB-C connection cable, USB 3.2 Gen1, 4K / 60 Hz, 1m

DB-300220-010-S

EAN 4016032481164



USB 3.2 Gen1, USB-C Connectioncable, 1m, 4K@60Hz Aluminum, PD60W

The Digitus® USB 3.0 Gen.1 connection cable is the all-rounder among cables. Thanks to the Thunderbolt 3 protocol, PCI Express, DisplayPort and host-to-host transmissions can be realized. You can use this cable to transfer audio/video signals, data and power. The data transfer speed is 5 Gbit/s. This allows you to transfer large data such as movies and music within seconds. The video signals are transmitted in max. 4K at a refresh rate of 60 Hz. Thanks to USB Power Delivery, the charging function is guaranteed. With the corresponding charger, you can charge your smart devices with max. 60 W (3 A / 20 V) in a short time. The USB Type-C interface enables broad compatibility with devices with this connection.

Supports the following transmission types: Audio/video/data transmission/charging function

- USB 3.2 Gen1
- Supports: 4K @ 60Hz
- Supports data transfer rates of up to 5 Gbit/s
- Backwards compatible with Thunderbolt 3 and USB 2.0
- Supports USB Power Delivery with 20V, 3A and 60W
- Core material: CU
- Color connections: Gray
- OD: 4.3 mm
- Material: TPE
- Operating temperature: -20°C - 60°C
- Storage temperature: -10°C - 50°C
- Humidity: 95%
- Bending radius: 60
- Tensile strength: 4Kg/min
- Manufacturer's instructions:
- If you connect a USB-C monitor/TV/projector to a PC equipped with USB Type-C, please make sure that your USB-C display supports DisplayPort signal output.
- The video output capability depends on the graphics card of your notebook and the connected monitor. Some monitors also limit the available resolution.

Attributes

- AWG: 32
- Feritni filtar: nema
- Kabel u boji: crni
- Konektor 1: USB C, utikač
- Konektor 2: USB C, utikač
- Površina konektora: poniklano
- USB sukladnost: USB 3.0 / 3.1
- Duljina: 1 m
- oklop: dvostruki oklop

Package contents

- 1x USB 3.0 Gen.1, USB Type -C connection cable (1m)

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	90	4.40	34.00	37.00	31.00	38,998.00
Packaging Unit Inside	1	0.05	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.05	11.00	12.00	3.00	396.00
Net single without Packaging	1	0.03	10.00	11.00	2.00	0.00

More images:











Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com