

DIGITUS® Enfas 32 A - laddkabel, typ 2 till typ 2

DK-1P32-075

EAN 4016032481409



Fordon - enfas, 240 V, 32 A, 7,5 m Fordonsladdkabel, 7,5 m, typ 2 till typ 2

Med fordonsladdkabeln Digitus DK-1P32-075 ansluter du utan problem alla fordon med typ 2-kontakt till offentliga laddstationer eller väggbboxar med ladduttag. Typ 2-laddkablarna är certifierade enligt EN 62196-1:2014, EN 62196-2:2017 och skyddsklass IP55.

Laddkabel typ 2 till typ 2, IP55-skyddsklass, 1-fas, t.o.m. 32 A.

- Typ: Standardkabel
- Kabellängd: 7,5 m
- Användbar längd: 7,5 m
- Typ av laddningskabel: 3 x 6 mm² + 1 x 0,75 mm²
- Färg: Svart

- Mantel: TPU
- Stickpropp: EN 62196-2 typ 2
- Nominell spänning: 230 V
- Nominell effekt: 7,4 kW
- Märkström: 32 A
- Anslutningsfaser: 1
- Driftstemperatur: -30 °C +50 °C
- Skyddsklass: IP55 (skyddad mot vattenstrålar)




Package contents

- 7,5 m fordonsanslutningskabel typ 2
- Snabbstartsguide

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	5	20.85	63.00	38.00	38.00	90,972.00
Packaging Unit Inside	1	4.17	0.00	0.00	0.00	0.00
Packaging Unit Single	1	4.17	35.00	35.00	15.00	18,375.00
Net single without Packaging	1	3.49	0.00	0.00	0.00	0.00

More images:



EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com