

DIGITUS USB 2.0 - USB C to Lightning Spiral Cable

AK-600434-006-S
EAN 4016032482567



USB - C to Lightning Spring cableý MFI C94 TPU USB 2.0, PD20W Max 1m, bl

With the DIGITUS® USB 2.0 - USB C to Lightning Spiral Cable, you can charge your devices with a Lightning connector. The charging power is 20W (20V/3A). In addition, you can synchronize your data with the PC or notebook at a data transfer rate of 480 Mbps. Thanks to the flexible length and spiral design, it can be used anywhere. Perfect in the car to charge your smartphone or as a spare cable for your desk, since the cable is easy to store anywhere.

Flexible and highly robust spiral cable for charging and synchronizing - 100% MFI-certified, compatible with all Lightning devices

- Supports the USB PD (Power Delivery) specification - charging power of 20W (5V/3A)
- USB Type-C plug can be used on both sides
- Cable length: 0.32m
- Usable length/extendable up to: 1m

Attributes

- Color cable: black
- Connector 1: Apple Lightning 8-pin, plug
- Connector 2: USB C, plug
- Connector surface: nickel-plated
- Hoods: plastic
- Length: 1 m

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	200	6.67	44.00	51.50	29.00	65,714.00
Packaging Unit Inside	1	0.03	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.03	21.00	11.50	1.80	434.70
Net single without Packaging	1	0.03	1.00	100.00	1.00	0.00

More images:



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schöffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com