

DIGITUS® 4K HDBaseT™ HDMI KVM extender set, 150 m

DS-55522

EAN 4016032483694



HDBaseT KVM Extender Set, 150 m 4K/60Hz, USB 1.1, PoC, IR, black

The HDBaseT™ HDMI KVM Extender Set enables uncompressed and high-resolution AV signal transmission over long distances via a CAT6 (or higher) network cable. The maximum transmission distance is 150 m. Thanks to PoC, only one unit needs to be powered with an external power supply unit. The receiver unit has two USB (1.1) ports for connecting a mouse & keyboard to control the signal source conveniently from the output display. Bi-directional IR transmission is also included.

The HDBaseT™ Extender Set enables uncompressed and high-resolution AV signal transmission over long distances and offers KVM functionality (mouse & keyboard connection)

- Supports HDBaseT™ 1.0 via CAT6A/7/8 cable up to 100 m
- Transmission distance - Full HD (1080p/60Hz): 150 m (max.)
- Transmission distance - UHD (4K/60Hz): 120 m (max.)
- Supports 4K2K/60Hz (4:4:4)
- Video bandwidth: 18 Gbps
- HDMI 2.0b / HDCP 2.2
- USB 1.1
- HDR, HDR10, HDR10+, DolbyVision, HLG
- PoC (Power over Cable) - only one unit requires an external power supply unit
- Connection of mouse & keyboard to the receiver for convenient control of the signal source from the output display
- EDID support (2 modes) - 1: Copy - HDMI output receiver / 2: Standard - 1080p, 2 channel
- Bi-directional IR signal transmission
- Transmitter unit connections:
 - 1x HDMI input (4K/60Hz) - Signal source connection
 - 1x RJ45 (HDBaseT™) output - CAT transmission cable connection
 - 1x IR input for receiving remote control signals
 - 1x IR output to control the source device
 - 1x USB-B (1.1) - PC connection (signal source) for using the KVM function
 - 1x power supply input (DC 24V/1A), screw connector - external power supply connection
 - 1x Micro USB input - Service/FW update
 - 1x EDID switch

- Receiver unit connections:
 - 1x HDMI output (4K/60Hz) - Output device connection
 - 1x RJ45 input - CAT transmission cable connection
 - 1x IR input for receiving remote control signals
 - 1x IR output to control the source device
 - 2x USB-A (1.1) - connection of mouse & keyboard
 - 1x power supply input (DC 24V/1A), screw connector - external power supply connection
 - 1x Micro USB input - Service/FW update
- Suitable for wall mounting
- ESD protection
- Operating temperature: 0-40°
- Power consumption: approx. 10W
- Compression: HDBaseT 1.0
- Housing: Metal
- Dimensions (1 unit): L 6.5 x W 14 x H 1.8 cm
- Weight (1 unit): 246 g
- Color: black

Attributes

- HDTV-norma: Full HD
- rezolucija maks.: 3840 x 2160 piksela, 60 Hz
- Kategorija: CAT 6
- KVM: Da
- PoE (napajanje preko Ethernet): Ne
- Priključci za video vezu: HDMI
- Razmak: 100 m
- Tehnologija prijenoša: CAT

Package contents

- 1x transmitter unit
- 1x receiver unit
- 1x IR transmitter cable (1.5 m)
- 1x IR receiver cable (1.5 m)
- 1x power supply unit (DC 24V/1A, 1.15 m)
- 1x USB connection cable (1.5 m)
- 1x mounting material
- 1x operating instructions

