

DIGITUS® Repetidor DisplayPort 8K

DS-55524

EAN 4016032483717



Repetidor DisplayPort 8K 30 m

O repetidor permite-lhe prolongar um sinal DP até 30 metros. Está em conformidade com a norma VESA DisplayPort 1.4 e suporta resoluções até 8K/30Hz. A alimentação é efectuada através de USB, utilizando o cabo fornecido.

Prolonga um sinal DP até 30 m

- 1x entrada DP
- 1x saída DP
- 1x entrada USB-C
- Resoluções suportadas: 8K/30Hz, 4K/120Hz, 4K/60Hz
- Extensão de distância 8K/30Hz: até 15 m (cabo DP AWG 28 ou superior)
- Extensão de distância 4K/60Hz: até 30 m (cabo DP AWG 28 ou superior)
- Suporta HDR (High Dynamic Range)

- VESA DisplayPort 1.4
- Alimentação eléctrica através de cabo USB
- Débitos de dados: 1,62 Gbps/2,7 Gbps/5,4 Gbps/8,1 Gbps
- Caixa: Alumínio
- Dimensões: C 6 x L 2,3 x A 1,8 cm
- Peso: 17 g
- Cor: Prateado

Attributes

- KVM: no
- PoE (Power over Ethernet): no

Package contents

- 1x repetidor DisplayPort 8K
- 1x cabo USB, 80 cm
- 1x QIG

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	100	28.20	30.00	25.00	39.50	29,625.00
Packaging Unit Inside	1	0.28	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.28	7.50	2.30	11.00	189.75
Net single without Packaging	1	0.02	1.10	2.30	6.00	0.00

More images:



Safety notes

- If the device is powered by a plug-in power supply, ensure that the power adapter is connected correctly and meets the specified requirements (e.g. voltage and current).
- Only use certified CAT5e or CAT6 cables to ensure stable signal transmission.
- For particularly long cable runs or in environments prone to interference, it is recommended to use shielded network cables.
- Make sure that all connections are tight and secure to avoid loose contacts that could affect the signal quality. Make sure that the HDMI and Ethernet connections are connected correctly.
- Make sure that the CAT cable is not laid near high-voltage power lines or other strong sources of electromagnetic interference to avoid signal interference.
- Only operate the device within the specified temperature range.
- Do not use the device outdoors or in damp or wet environments
- Check all connections and cables regularly for wear or damage. Cables and connections can wear out, especially with frequent use or long installations, which can lead to poor signal quality or system failure.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
 info@assmann.com