

DIGITUS USB Type C to DisplayPort adapter cable

DB-300334-010-S
EAN 4016032484264



8K@30Hz. USB Type C to DP, adapter cable HBR3, Aluminum Housing, Black 1m

The DIGITUS® USB Type C DisplayPort adapter cable supports the transfer from a USB Type C source to a DisplayPort interface. For example, you can connect your laptop (USB Type-C equipped) to your monitor, TV or projector (DisplayPort interface). Power is supplied via the USB port, so no external power source is required.

The DIGITUS® USB Type-C to DisplayPort adapter cable supports the transfer of USB Type-C sources to DP-capable displays.

- Supports: Resolutions up to 8K (7680x4320) at a refresh rate of 30Hz.
- Supports: Resolutions up to 4K at 144Hz
- Supports: Resolutions up to 2K at 165Hz
- Transmission speed: 25.92 Gbit/s
- Supports the transmission of audio and video signals
- Aluminum housing
- Ferrite filter: none
- USB-C products: yes
- Copper cores, foil and braid shielded for robustness and a reliable connection
- DisplayPort Standard: DP 1.4

- USB standard: USB4 Gen2 20Gbps
- Supported: Multi-Stream Transport (MST)
- Manufacturer's instructions:
- If you connect a USB-C monitor/TV/projector to a DP-equipped PC, please make sure that your USB-C display supports DisplayPort signal output.
- The video output capability depends on the graphics card of your notebook and the connected monitor. Some monitors also limit the available resolution.
- AOC - Active optical cable: no

Attributes

- AWG: 34
- Color cable: black
- Connector 1: USB C, plug
- Connector 2: DP, plug
- Ferrite filter: none
- USB compliance: USB Type-C™
- Length: 1 m
- Shielding: triple shielding

Package contents

- 1x USB Type-C adapter cable, USB Type-C to DP, 1m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	120	7.60	49.00	52.00	25.00	63,700.00
Packaging Unit Inside	1	0.06	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.06	2.30	7.50	23.50	405.38
Net single without Packaging	1	0.04	2.00	7.00	21.50	0.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schöffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com