

# DIGITUS® 4K USB Adapter, USB-C plug to HDMI-A jack

AK-300450-000-S

EAN 4016032486169



### USB-Type-C-Adapter,USB-C to HDMI Type-A, 4K@30HZ Aluminum housing, black

The DIGITUS® 4K USB-C Adapter enables you to connect your notebook or tablet to a monitor, projector or TV device to the USB-C connection. No additional adapters are required. Depending on the source device, this adapter supports resolutions of up to 4K / 3840 x 2160 with a display refresh rate of 30 Hz. incl. 3D and ARC support.

### Converts audio/video signals to HDMI signal in UHD 4K via the USB-C interface.

- Transmits an HDMI signal in UHD 4K via the USB-C interface
- Supports 4K / 30 Hz
- Plug and Play - no driver installation required
- Elegant aluminum housing
- Your device equipped with USB-C must support the DisplayPort video mode (DP Alt Mode) in order to be compatible with this adapter/converter.

- The video output capabilities depend on your notebook's graphic card and the connected monitor. Some screens also limit the available resolution.

### Attributes

- Feritni filter: nema
- HDTV-norma: Ultra HD 4K
- Kabel u boji: crni
- Konektor 2: HDMI tip A, priključak
- Površina konektora: pozlaćeno
- rezolucija maks.: 3840 x 2160 piksela, 30 Hz
- Duljina: 0.05 m
- AOC - aktivni optički kabel: Ne

### Package contents

- 4K USB Adapter, USB-C plug to HDMI-A jack

### Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	50	0.90	18.00	24.00	31.00	13,392.00
Packaging Unit Inside	25	0.45	16.00	11.00	29.00	5,104.00
Packaging Unit Single	1	0.02	3.00	5.50	10.00	165.00
Net single without Packaging	1	0.01	0.00	0.00	0.00	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)