

# DIGITUS® DIGITUS Industrial Gigabit Media Converter RJ45, SC 20 km

DN-652102-1

EAN 4016032488194



### Industrial Gigabit Ethernet Media Converter, SM SC connector, 1310nm, up to 20 km

The media converters from DIGITUS® are an optimal solution for the migration of fiber optic signals. You can now access fiber optic technology and bridge several kilometers without having to replace your entire network cabling. With our extensive range of products, you can respond to your individual requirements. Intuitive operation guarantees quick and easy installation. Years of experience and a wide range of products make DIGITUS® a reliable partner for your network technology.

### Industrial Gigabit media converter 10/100/1000BaseT to 1000Base-SX SC, singlemode 1310 nm up to 20 km, The perfect converter solution for optical data transmission

- Converts wire-based network signals into fiber optic signals
- High quality and maximum reliability
- 10/100/1000Base-TX to 1000Base-SX
- Connections: 1x RJ45, 1x SC Duplex
- Range up to 20 km
- Wavelength: 1310nm
- Singlemode dual fiber
- Automatic cable detection - Auto MDI / MDI-X function
- Diagnostic LEDs for status and activity monitoring
- Suitable for 9/125µm fiber optic cable (multimode)
- Compact, robust metal housing
- Excellent protection against short circuits
- Lightning protection and surge protection
- Redundant power supply: 12-48 V DC, redundant power supply with polarity reversal protection function

- Extended operating temperature range, -40 °C ~ +80 °C
- Protection class IP40
- Connection 1: RJ45
- Connection 2: SC
- Mode: Singlemode
- Distance (km): 2
- DDM support: no
- Industrial use: yes
- Transmission method: Unidirectional
- PoE injector: no
- Ethernet speed: Gigabit
- Product dimensions: 118x 92.4 x 40 mm
- Power consumption: <3 W

#### Attributes

- Connector 1: RJ45
- Connector 2: SC
- Distance (km): 20
- Wavelength: 1310 nm
- DDM Support: no
- Industrial usage: yes
- PoE injector: no
- Ethernet speed: Gigabit

#### Package contents

- Industrial Gigabit media converter RJ45, SC 20 km
- User manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	24	14.60	46.50	39.50	24.00	44,082.00
Packaging Unit Inside	1	0.61	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.61	5.40	13.50	16.50	1,202.85
Net single without Packaging	1	0.46	3.40	8.60	12.80	0.00

**More images:**



**Safety notes**

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
 info@assmann.com