

DIGITUS® Dynamic-N series wall-mounted enclosure - 600x450 mm (WxD), unassembled

DN-37100

EAN 4016032488538



7U wall mounting cabinet, Dynamic 600 x 450 mm, unmounted, grey

Zidni komunikacijski ormari Dynamic Basic proizvedeni su od čvrste čelične konstrukcije. Vareni spojevi osiguravaju stabilnost. Bočni dijelovi mogu se skinuti, a ormar na zid možete jednostavno i brzo montirati. Zahvaljujući fleksibilnosti, ormari su idealni za sve trenutne IT i telekomunikacijske primjene.

The unassembled delivery of the wall-mounted enclosures ensures optimized transport options. Assembly can be carried out quickly and easily.

- Protection class IP20
- Lockable safety glass door with steel frame
- 230° door opening angle
- 1-point locking on the front door
- 483 mm (19") profile rails at the front and rear inside the enclosure, galvanized
- 483 mm (19") profile rails are adjustable in depth and marked with the height unit
- 1.0 - 1.2 mm robust sheet steel with high load-bearing capacity, powder-coated
- Cable entry possible at the rear, roof and base (pre-punched cut-outs)
- Roof is prepared to accommodate a fan element (punched-out mounts)

- Ventilation slots for active and passive ventilation
- 4 earthing points (base, side panel and front door) with protective cap
- Installation depth for components (standard maximum): 219 - 320 mm

Attributes

- Bočne ploče: Obje strane
- Boja: svijetlo siva, RAL 7035
- Dubina: 450 mm
- Jedinice: 7
- Kapacitet opterećenja: 60 kg
- Prednja vrata: Staklena vrata, jednostruko otvaranje
- Širina: 600 mm
- Stražnja vrata: Stražnja ploča
- Vrsta ormara: Zidni ormarić
- IP klasa zaštite: IP20
- Montirano: Ne

Package contents

- Earthing cable set
- Installation set (screws, cage nuts, washers)
- 2 x key
- Assembly instructions

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	17.00	52.00	65.00	28.00	94,640.00
Packaging Unit Inside	1	17.00	52.00	65.00	28.00	94,640.00
Packaging Unit Single	1	17.00	52.00	65.00	28.00	94,640.00
Net single without Packaging	1	14.80	45.00	60.00	38.50	0.00

More images:

Digitus WALL MOUNTING CABINET DYNAMIC-N SERIES

HU	Height	Width	Depth
7	385 mm	600 mm	450 mm / 600 mm
9	474 mm		
12	607 mm		
16	785 mm		

Available in 2 colors: Grey (RAL 7035) and Black (RAL 9005)

Digitus EASY WALL MOUNTING
Mounted in only two steps

1. Screw the supplied mounting plate to the wall.
2. Connect the housing to the wall mounting plate.

Digitus

Includes 4 x 483 mm (19") profile rails for optimal cabinet expansion

Cable entry possible via the top, base and rear side

Digitus

Ventilation slots for passive ventilation, roof prepared for active fan unit

230° door opening angle

Lockable front door with certified safety glass

Digitus FAST AND INTUITIVE ASSEMBLY
Delivery in logistically optimized flat packaging

1. Assembly of the base panel with front & rear structural frames
2. Assembly of the top cover (roof) with front & rear structural frames
3. Installation of 4 mounting profiles for 19" accessories
4. Installation of side panels, side panel hooks and front door hinges

Digitus WALL MOUNTING CABINET DYNAMIC-N | 7U

19" Installation

Passive Ventilation

IP20 Protection Class



Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be laid neatly and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.

- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com