

# DIGITUS® Dynamic-N series wall-mounted enclosure - 600x450 mm (WxD), unassembled

DN-37100

EAN 4016032488538



## 7U wall mounting cabinet, Dynamic 600 x 450 mm, unmounted, grey

Zidni komunikacijski ormari Dynamic Basic proizvedeni su od čvrste čelične konstrukcije. Vareni spojevi osiguravaju stabilnost. Bočni dijelovi mogu se skinuti, a ormar na zid možete jednostavno i brzo montirati. Zahvaljujući fleksibilnosti, ormari su idealni za sve trenutne IT i telekomunikacijske primjene.

**The unassembled delivery of the wall-mounted enclosures ensures optimized transport options. Assembly can be carried out quickly and easily.**

- Protection class IP20
- Lockable safety glass door with steel frame
- 230° door opening angle
- 1-point locking on the front door
- 483 mm (19") profile rails at the front and rear inside the enclosure, galvanized
- 483 mm (19") profile rails are adjustable in depth and marked with the height unit
- 1.0 - 1.2 mm robust sheet steel with high load-bearing capacity, powder-coated
- Cable entry possible at the rear, roof and base (pre-punched cut-outs)
- Roof is prepared to accommodate a fan element (punched-out mounts)

- Ventilation slots for active and passive ventilation
- 4 earthing points (base, side panel and front door) with protective cap
- Installation depth for components (standard maximum): 219 - 320 mm

### Attributes

- Bočne ploče: Obje strane
- Boja: svijetlo siva, RAL 7035
- Dubina: 450 mm
- Jedinice: 7
- Kapacitet opterećenja: 60 kg
- Prednja vrata: Staklena vrata, jednostruko otvaranje
- Širina: 600 mm
- Stražnja vrata: Stražnja ploča
- Vrsta ormara: Zidni ormarić
- IP klasa zaštite: IP20
- Montirano: Ne

### Package contents

- Earthing cable set
- Installation set (screws, cage nuts, washers)
- 2 x key
- Assembly instructions

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	17.00	52.00	65.00	28.00	94,640.00
Packaging Unit Inside	1	17.00	52.00	65.00	28.00	94,640.00
Packaging Unit Single	1	17.00	52.00	65.00	28.00	94,640.00
Net single without Packaging	1	14.80	45.00	60.00	38.50	0.00

More images:



**Digitus**  
**FAST AND INTUITIVE ASSEMBLY**  
Delivery in logistically optimized flat packaging

**Digitus**

Ventilation slots for passive ventilation, roof prepared for active fan unit

230° door opening angle

Lockable front door with certified safety glass

**Digitus**

**WALL MOUNTING CABINET DYNAMIC-N | 7U**

- Single termination
- Passive ventilation
- IP20 Protection Class

Includes 4 x 4.83 mm (19") profile rails for optimal cabinet expansion

Cable entry possible via the top, base and rear side

**Digitus**  
**EASY WALL MOUNTING**  
Mounted in only two steps

1. Screw the supplied mounting plate to the wall.
2. Connect the housing to the wall mounting plate.

**Digitus**  
**WALL MOUNTING CABINET DYNAMIC-N SERIES**

HU	Height	Width	Depth
7	385 mm	600 mm	450 mm / 600 mm
9	474 mm		
12	607 mm		
16	785 mm		

Available in 2 colors: Grey (RAL 7035) and Black (RAL 9005)

**Safety notes**

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be laid neatly and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.

- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)