

# DIGITUS® Comutador PoE Gigabit Ethernet industrial de 4+2 portas

DN-651149

EAN 4016032489252



## Comutador PoE Gigabit Ethernet industrial de 4+2 portas 4 portas GE PoE RJ45, 2 portas GE SFP

O DN-651149 é um robusto comutador Industrial Gigabit Ethernet PoE de 4+2 portas para ambientes agressivos. Com desempenho de velocidade de fio sem bloqueio, oferece 4x 10/100/1000 BASE-TX RJ45 (até 30 W PoE cada) + 2x 1000 portas Base-Fx. A caixa IP40 com fonte de alimentação redundante é ideal para monitoramento, gerenciamento de controle e serviços sem fio de -40 °C a 80 °C.

**4 x PoE 10/100/1000 BASE-TX RJ45 + 2x portas 1000Base-Fx. A caixa IP40 com fonte de alimentação redundante é ideal para monitoramento, gerenciamento de controle e serviços sem fio de -40 °C a 80 °C.**

- Suporta controlo de fluxo IEEE802.3x e contrapressão
- Suporta a tecnologia store-and-forward para uma transmissão de dados otimizada
- Detecção/ajuste automático de velocidade e half/full duplex
- 4 portas PoE com até 30 W
- Largura de banda: 14 Gbps
- Buffer de pacotes: 1,2 Mbit
- Tamanho do encaminhamento de pacotes: 10,5 Mbps
- Tamanho da tabela de endereços MAC: 2K
- Velocidade de fotogramas Jumbo: 9000 bytes
- Proteção ESD: 6 kV (DC)
- Proteção EFT: 6 kV (DC)
- Caixa metálica, IP40
- Proteção contra raios e sobretensões de 4 kV

- Fonte de alimentação redundante com função de proteção contra polaridade inversa
- Fonte de alimentação: 48 a 57 V
- Consumo de energia: <5 W
- Ligação de terminal amovível
- Grau de proteção: IP40
- Dimensões: 142,5 x 107,1 x 53,5 mm
- Temperatura de funcionamento: -40 a 80 °C
- Temperatura de armazenamento: -40 a 80 °C
- Humidade: 5% a 95% (sem condensação)
- MTBF: 300.000

### Attributes

- Number of ports: 4
- PoE Power budget: 100 W
- PoE standard: IEEE802.3af (PoE)
- Ethernet speed: Gigabit
- Industrial usage: yes
- Managed: no
- Number of ports (Uplink): 2
- Outdoorsuitable: no
- PoE (Power over Ethernet): yes
- Protection against vandalism: no
- Uplink port connection: RJ45/SFP
- VLAN: no

### Package contents

- 1x Switch Industrial Gigabit Ethernet PoE
- 1x manual do utilizador

## Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	14	12.27	46.50	39.50	24.00	44,082.00
Packaging Unit Inside	1	0.88	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.88	6.60	15.80	21.30	2,221.16
Net single without Packaging	1	0.70	4.40	10.30	14.40	0.00

**More images:**



**Safety notes**

- This product is intended for indoor use only.
- Read all instructions and follow all warnings and instructions on the device.
- Do not place this appliance on an unstable surface (such as a trolley, stand, table, etc.).
- Do not use this appliance near water.
- Do not place this appliance near or above a radiator.
- The housing is equipped with openings for heat dissipation and ventilation. To prevent overheating during operation, the ventilation openings must not be blocked or covered.
- Do not place the appliance on a soft surface (e.g. bed, sofa, blanket, etc.). This will block the ventilation.
- The appliance must not be installed in a closed environment if adequate ventilation is not guaranteed.
- Do not spray any liquids onto the appliance.
- Disconnect the mains plug before cleaning. Do not use any liquid or foam cleaners.
- Clean the appliance with a damp cloth.
- Connect the device according to the power supply on the rating plate.
- To prevent damage to the appliance, it is important that all appliances are properly earthed.
- Do not place any objects on the power cable and lay it in such a way as to avoid tripping hazards.
- Use a surge protector, a regulator or an uninterruptible power supply (UPS) to protect your system from sudden, temporary and reduced power.
- Secure the system cable and mains cable properly and ensure that no objects are pressing on the cable.
- Do not insert any objects into the appliance through the openings in the housing. There is a risk of a short circuit, which can lead to fire or electric shock.
- Do not attempt to repair the appliance yourself. Always contact an authorized customer service centre.
- If any of the following conditions occur, unplug the appliance and send it to an authorized service centre for repair
  - The mains cable, power supply unit or plug for the power supply is damaged or worn;
  - Liquid has penetrated the appliance;
  - The device has been exposed to rain or water;
  - The device has been dropped or the housing has been damaged;
  - The function of the device has obviously changed;
  - The appliance cannot be operated as described in the operating instructions.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)