

DIGITUS® Comutador Fast Ethernet industrial de 8+2 portas

DN-651146

EAN 4016032490265



Comutador Fast Ethernet industrial de 8+2 portas 8 portas FE RJ45, 2 portas GE SFP

O DN-651146 é um robusto comutador Ethernet Industrial de 8+2 portas para ambientes agressivos. Com desempenho de velocidade de fio sem bloqueio, oferece 8x 10/100BASE-TX RJ45 + 2x portas 1000Base-Fx. A caixa IP40 com fonte de alimentação redundante é ideal para monitoramento, gerenciamento de controle e serviços sem fio de -40 °C a 80 °C.

8x 10/100BASE-TX RJ45 + 2x portas 1000Base-Fx. A caixa IP40 com fonte de alimentação redundante é ideal para monitorização, gestão de controlo e serviços sem fios entre -40 °C e 80 °C.

- Suporta controlo de fluxo IEEE802.3x e contrapressão
- Suporta a tecnologia store-and-forward para uma transmissão de dados otimizada
- Detecção/definição automática de velocidade e half/full duplex
- Largura de banda: 5,6 Gbps
- Buffer de pacotes: : 1,2 Mbit
- Tamanho do encaminhamento de pacotes: 4,2 Mbps
- Tamanho da tabela de endereços MAC: 2K
- Velocidade de fotogramas Jumbo: 9000 bytes
- Proteção ESD: 6 kV (DC)
- Proteção EFT: 6 kV (DC)
- Caixa metálica, IP40
- Proteção contra raios e sobretensões de 4 kV
- Fonte de alimentação redundante com função de proteção contra polaridade inversa

- Fonte de alimentação: 12 a 48 V
- Consumo de energia: < 8 W
- Ligação de terminal amovível
- Grau de proteção: IP40
- Dimensões: 143,7 x 104 x 47,7 mm
- Temperatura de funcionamento: -40 a 80 °C
- Temperatura de armazenamento: -40 a 80 °C
- Humidade: 5% a 95% (sem condensação)
- MTBF: 300.000

Attributes

- Number of ports: 8
- Ethernet speed: Fast Ethernet
- Industrial usage: yes
- Installation type: DIN rail
- Managed: no
- Number of ports (Uplink): 2
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vandalism: no
- Uplink port connection: SFP
- VLAN: no

Package contents

- 1x Switch Industrial Fast Ethernet
- 1x manual do utilizador

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	15	11.40	46.50	39.50	24.00	44,082.00
Packaging Unit Inside	1	0.76	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.76	6.60	15.80	21.30	2,221.16
Net single without Packaging	1	0.60	4.80	10.40	14.40	0.00

More images:



Safety notes

- This product is intended for indoor use only.
- Read all instructions and follow all warnings and instructions on the device.
- Do not place this appliance on an unstable surface (such as a trolley, stand, table, etc.).
- Do not use this appliance near water.
- Do not place this appliance near or above a radiator.
- The housing is equipped with openings for heat dissipation and ventilation. To prevent overheating during operation, the ventilation openings must not be blocked or covered.
- Do not place the appliance on a soft surface (e.g. bed, sofa, blanket, etc.). This will block the ventilation.
- The appliance must not be installed in a closed environment if adequate ventilation is not guaranteed.
- Do not spray any liquids onto the appliance.
- Disconnect the mains plug before cleaning. Do not use any liquid or foam cleaners.
- Clean the appliance with a damp cloth.
- Connect the device according to the power supply on the rating plate.
- To prevent damage to the appliance, it is important that all appliances are properly earthed.
- Do not place any objects on the power cable and lay it in such a way as to avoid tripping hazards.
- Use a surge protector, a regulator or an uninterruptible power supply (UPS) to protect your system from sudden, temporary and reduced power.
- Secure the system cable and mains cable properly and ensure that no objects are pressing on the cable.
- Do not insert any objects into the appliance through the openings in the housing. There is a risk of a short circuit, which can lead to fire or electric shock.
- Do not attempt to repair the appliance yourself. Always contact an authorized customer service centre.
- If any of the following conditions occur, unplug the appliance and send it to an authorized service centre for repair
- The mains cable, power supply unit or plug for the power supply is damaged or worn;
- Liquid has penetrated the appliance;
- The device has been exposed to rain or water;
- The device has been dropped or the housing has been damaged;
- The function of the device has obviously changed;
- The appliance cannot be operated as described in the operating instructions.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com