

DIGITUS Universal 19-Inch Equipment Rack with Castors, 8U

DN-48000

EAN 4016032490302



8U AVS rack, 420 x 507 x 460 mm threaded mounting holes, castors, bl

The 19-inch racks from DIGITUS® can be used universally thanks to their 19-inch thread perforation. Audiovisual accessories (AVS) or active and passive network components can be installed in the blink of an eye without needing captive nuts. The thread perforation of the profiles enables compatibility with US or EU screw sizes. Both screw types are included in delivery. Durable sheet steel design ensures the necessary robustness and allows maximum loads of up to 136 kg. Ventilation slits on both side walls ensure passive cooling of installation components. Equipped with rollers and carrying handles, the 19-inch racks are portable as needed for optimal positioning. Delivery is carried out as an unassembled flat pack to optimize logistics effort. The rack is easy and quick to assemble thanks to the included screwdriver and simple design. The portfolio includes various sizes to meet any requirements.

The 19-inch racks from DIGITUS® can be used universally thanks to their 19-inch thread perforation. Audiovisual accessories (AVS) or active and passive network components can be installed in the blink of an eye. Compatible with US or EU screw sizes

- 483 mm (19") thread perforation on front and back side
- Compatible with US or EU screw sizes
- Robust design made of sheet steel with load capacity up to 136 kg

- Side walls with ventilation slits for passive cooling
- Including rollers and carrying handles
- Including screwdriver and 483 mm (19") dummy cover
- Unassembled delivery as flat pack
- Product dimensions (H x W x D): 420 x 507 x 460 mm
- Product dimensions flat pack (H x W x D): 160 x 515 x 477 mm
- Weight (net/gross): 13.2 kg / 14.7 kg
- Color: Black (RAL 9005)
- Installation depth for components max.: 457,8 mm
- Cabinet type: Network cabinet
- Color: black, RAL 9005
- Front door: without
- Load capacity: 136 kg
- Side panels: Both sides
- Units: 8
- Width: 507 mm
- IP protection class: without
- Mounted: no

Package contents

- 1 x Rack
- 1 x Screwdriver
- 1 x QIG
- 1 x Set installation screws
- 1 x Set installation screws

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	13.90	54.00	49.50	13.50	36,085.50
Packaging Unit Inside	1	13.90	54.00	49.50	13.50	36,085.50
Packaging Unit Single	1	13.90	54.00	49.50	13.50	36,085.50
Net single without Packaging	1	12.80	46.00	47.70	42.00	0.00

A black server rack on wheels. The front panel is open, revealing internal components. At the top, there are two rows of ports: a row of 8 RJ45 ports on the left and a row of 8 SFP ports on the right. Below these, there are two rows of 16 ports each, likely for fiber optics. A black power supply unit is mounted in the center. At the bottom, there is a row of 16 red circular ports, likely for power or data. The rack is mounted on four casters.

