

DIGITUS® Suporte de parede para equipamento de 19 polegadas, 4U

DN-48004

EAN 4016032490340



Estrutura de montagem na parede 4U, vertical 194 x 504 x 151 mm, preto

Os suportes de 19 polegadas da DIGITUS® permitem que o seu equipamento seja posicionado verticalmente na parede. Isto é ideal quando o espaço é escasso. Em alternativa, pode montar o suporte por baixo de uma mesa, por exemplo, e colocar o seu equipamento na horizontal para poupar espaço. Esta é a forma ideal de realizar estações de trabalho, configurações de streaming, etc. Os acessórios de áudio e vídeo (AVS) ou os componentes de rede activos e passivos podem ser montados num instante. O portefólio inclui vários tamanhos para satisfazer todas as necessidades.

Os suportes de 19 polegadas da DIGITUS® permitem que o seu equipamento seja posicionado verticalmente na parede. Em alternativa, os aparelhos podem ser montados horizontalmente, por exemplo, debaixo da mesa.

- Construção robusta em chapa de aço com uma capacidade de carga até 30 kg
- Dimensões do produto (A x L x P): 194 x 504 x 151 mm

- Dimensões do produto, incluindo a embalagem (A x L x P):
- Peso (líquido/bruto): 0,72 kg / 1,3 kg
- Cor: Preto (RAL 9005)

Attributes

- Cabinet type: Wall Mounting Brackets
- Color: black, RAL 9005
- Depth: 151 mm
- Front door: without
- Load capacity: 30 kg
- Side panels: Without
- Units: 4
- Width: 504 mm
- IP protection class: without
- Mounted: yes

Package contents

- 1 x suporte de 19 polegadas
- 1 x conjunto de parafusos de equipamento

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	6	9.20	63.50	53.00	34.50	116,110.00
Packaging Unit Inside	1	1.53	53.50	20.50	16.50	18,096.40
Packaging Unit Single	1	1.53	53.50	20.50	16.50	18,096.40
Net single without Packaging	1	1.30	15.10	50.40	19.40	0.00

More images:



Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com