

# DIGITUS Wall Mounting Cabinet SOHO PRO - 254 mm (10") - 315x300 mm (BxT)

DN-49100 EAN 4016032493624





### 10" 6U wall mounting cabinet, SOHO PRO 325 x 315 x 300 mm, grey

Whether for private areas, office or sub-distribution units with limited space: With the compact 254 mm (10") solutions from the SOHO PRO series, you can install your network wherever you like. The wall housings available in three rack units (6 rack units, 9 rack units, 12 rack units) are equipped with a full glass door as well as a cable entry in the roof and floor. A pair of galvanized 254 mm (10") profile rails labeled with easy-to-read rack units are installed on the inside. Their depth can be adjusted. Each cabinet features a robust steel design made of up to 1.5 mm thick sheet steel. Coloring is done with electrostatic powder coating in the standard colors gray (RAL 7035) or jet black (RAL 9005). The door hinges can be switched. The network are unassembled on delivery, in an optimized flat pack. Installation takes just a few steps and is extremely easy thanks to the step-by-step instructions included.

## The DIGITUS® Wall Housing SOHO PRO series is characterized by efficient delivery in an optimized flat pack as well as particularly user-friendly installation.

- Protection class IP20
- · Lockable safety glass door
- 200° door opening angle
- 1-point locking on the front door

- 254 mm (10") profile rails on the front, mounted on the front inside the cabinet, galvanized
- 254 mm (10") profile rails are adjustable in depth
- 1.1 1.5 thick sheet steel with high load capacity, powder-coated
- Cable entry with brush management panel in roof and plastic cover in floor
- Ventilation slits for active and passive ventilation
- Installation depth for components max.: 254 mm
- Product dimensions (H x W x D):  $325 \times 315 \times 300 \text{ mm}$
- Packaging dimensions (H x W x D): 175x 340x 360mm
- Weight (net/gross): 5,01 / 5,25 kg
- · Cabinet type: Wall mounting cabinet
- Color: light grey, RAL 7035
- Front door: Glass door, single opening
- · Load capacity: 60 kg
- Side panels: Both sides
- Units: 6
- Width: 316 mm
- IP protection class: IP20
- Mounted: no

#### **Package contents**

- Installation set (screws, captive nuts, washers)
- 2x Keys
- 2x Keys
- 1x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	5.25	34.00	36.00	17.50	21,420.00
Packaging Unit Inside	1	5.25	34.00	36.00	17.50	21,420.00
Packaging Unit Single	1	5.25	34.00	36.00	17.50	21,420.00
Net single without Packaging	1	5.01	30.00	31.50	32.50	0.00



### More images:





























