

DIGITUS® Hirose Modular Plug, CAT 6 TM 21 - 50 pieces

A-MO6-8-8-HRS-50

EAN 4016032494966



50x

Hirose Modular Plug, CAT 6 TM21 8P8C, shielded, for round cable, incl. hood, 50 pcs

These modular plugs can be used to establish quick and simple connections.

- Easy assembly by modular crimping tool DN-94008
- Layout performance: CAT 6, 1GBase-T
- Area of application: Patch cable assembly
- General properties:
- Fully shielded with strain relief for installation cables
- Incl. comb
- Technical properties:
- Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Material connector body: Polycarbonat, clear

- Connector contact: Phosphor bronze, brass 0.8 mm gold-plated
- Material shielding housing: Brass 0.5 mm, 2 mm nickel-plated
- Flammability: UL 94V-2
- Physical properties:
- Insertion force: 30N max. (IEC 60603-7-5)
- Diameter Cu-Conductor: AWG (27/7 ... 24/7)
- Operating temperature: -20 °C to +60 °C
- Current carrying capacity: 1A at 50 °C
- Diameter outer jacket: 5,5 ... 6,2mm
- 50 pieces

Attributes

- Category: CAT 6

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	0.40	21.00	22.00	10.00	4,620.00
Packaging Unit Inside	1	0.40	21.00	22.00	10.00	4,620.00
Packaging Unit Single	1	0.40	21.00	22.00	10.00	4,620.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:



Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com