Digitus® USB-C silikonski spojni kabel, 1 m, crni

AK-300340-010-S
EAN 4016032495437

USB-C Silicone charging cable, USB-A - USB-C 1m, USB 2.0, 60W, black

Pouzdana i jednostavna veza između vaših USB-C uređaja i računala zahvaljujući mekanom i fleksibilnom silikonskom kabelu. Brzina prijenosa podataka od 480 Mbits/s za sinkronizaciju i prijenos podataka te specifikacija isporuke snage od 60 W za punjenje.

Brzo punjenje i sinkronizacija pomoću visokokvalitetnog, mekanog silikonskog priključnog kabela

- Podržava brzine prijenosa podataka od 480 Mbit/s
- Unazad kompatibilan s USB 2.0 i USB 1.1
- Podržava USB Power Delivery funkciju s 20 V, 3 A i 60 W
- Izdžljiv kabel s vijekom trajanja do 25.000 savijanja (temeljem internih testova)
- Type-C priključak može se koristiti s obje strane.

Attributes

- AWG: 24
- Kabel u boji: crni
- Kapice: ukalupljeno
- Konektor 1: USB A, utikač
- Konektor 2: USB C, utikač
- Materijal žice: CU
- Površina konektora: poniklano
- Duljina: 1 m
- oklop: jednostruki oklop

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	200	7.90	21.00	32.00	50.00	33,600.00
Packaging Unit Inside	10	0.40	3.60	24.00	30.00	2,592.00
Packaging Unit Single	1	0.04	1.00	21.00	11.50	240.29
Net single without Packaging	1	0.03	0.90	12.00	10.00	0.00

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

More images:





Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com