DIGITUS® 4K HDMI Splitter, 1x4

DS-55337

EAN 4016032495581



1x4 HDMI Splitter, 4K/60Hz HDCP 2.2, EDID Control

The DIGITUS® HDMI splitter distributes audio and video signals from your HDMI device to 4 TVs, monitors, or projectors at a resolution of UHD 4K/60Hz. Using EDID management, you can choose from 3 modes (Copy, Auto, Downscaler). The built-in downscaling feature supports the display of 4K content on Full HD displays; additionally, both 4K and Full HD displays can be used simultaneously. Thanks to the Auto-EDID feature, the splitter automatically detects the connected displays—no manual settings are required. The video splitter is powered via a USB-C cable, for example, from the source device or a USB charging adapter.

The DIGITUS® HDMI splitter distributes/mirrors audio and video signals from your HDMI device to 4 TVs, monitors, or projectors at a maximum resolution of 4K/60 Hz.

- Distributes an HDMI signal to 4 TVs, monitors, or projectors
- EDID Management: Auto/Copy/Downscaler
- Power supply via USB-C cable (included)
- Max. resolution: 4K/60 Hz (4:4:4)
- Video bandwidth: 18 Gbps
- Supports High Dynamic Range (HDR)
- Supports HDCP 2.2
- Supports Deep Color (36-bit)
- Supports compressed (e.g., DTS, Dolby Digital, etc.) and uncompressed audio formats (e.g., LPCM, etc.)
- HDMI 2.0
- Connections:
- 1x HDMI input (4K/60 Hz)
- 4x HDMI Outputs (4K/60 Hz)
- 1x Micro USB input (DC 5V) - Power supply
- 8 Status LEDs
- 1 EDID switch
- Operating temperature: 0–70°
- Power consumption: approx. 5W
- Housing: Metal
- Dimensions (housing): L 13.6 x W 6.1 x H 1.4 cm
- Weight: 182 g
- Color: black

Attributes

- Broj priključaka: 4
- HDTV-norma: Ultra HD 4K
- rezolucija maks.: 3840 x 2160 piksela, 60 Hz
- Izlaz signala: HDMI
- Priključci za video vezu: HDMI
- Ulaz signala: HDMI

Package contents

- 1 HDMI splitter
- 1 USB-C cable (1.0 m)
- 1 QIG

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	40	13.40	39.50	30.50	44.00	53,009.00
Packaging Unit Inside	1	0.34	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.34	17.90	12.30	4.50	990.77
Net single without Packaging	1	0.18	13.60	6.10	1.50	0.00

More images:










Safety notes

- If the device is powered by a plug-in power supply, ensure that the power adapter is connected correctly and meets the specified requirements (e.g. voltage and current).
- Only use certified CAT5e or CAT6 cables to ensure stable signal transmission.
- For particularly long cable runs or in environments prone to interference, it is recommended to use shielded network cables.
- Make sure that all connections are tight and secure to avoid loose contacts that could affect the signal quality. Make sure that the HDMI and Ethernet connections are connected correctly.
- Make sure that the CAT cable is not laid near high-voltage power lines or other strong sources of electromagnetic interference to avoid signal interference.
- Only operate the device within the specified temperature range.
- Do not use the device outdoors or in damp or wet environments
- Check all connections and cables regularly for wear or damage. Cables and connections can wear out, especially with frequent use or long installations, which can lead to poor signal quality or system failure.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com