

# DIGITUS® Cabo de silicone USB, USB 10Gbps, 1m, preto

AK-300342-010-S  
EAN 4016032496076



**Cabo de ligação USB de silicone, USB-C - USB-C 1m, USB 3.2 Gen2, 10G, 4K, 100W, preto**

Carregamento e sincronização rápidos com o cabo de ligação de silicone macio e de alta qualidade. A transmissão de vídeo 4K é possível com a versão USB 3.2 Gen2

**Carregamento e sincronização rápidos com o cabo de ligação de silicone macio e de alta qualidade. A transmissão de vídeo 4K é possível com a versão USB 3.2 Gen2**

- Suporta taxas de transferência de dados de 10 Gbps
- Retrocompatível com USB 3.1, USB 3.0, USB 2.0 e USB 1.1
- Suporta a função de fornecimento de energia USB com 20V, 5A e 100W
- Suporta 4K (3840x2160) @60Hz

- Cabo durável com uma vida útil de até 10.000 curvas (com base em testes internos)
- A ficha tipo C pode ser utilizada em ambos os lados

**Attributes**

- AWG: 31
- Color cable: black
- Connector 1: USB C, plug
- Connector 2: USB C, plug
- Connector surface: nickel-plated
- Ferrite filter: none
- USB compliance: USB 3.0 / 3.1
- Length: 1 m
- Shielding: triple shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	150	6.26	21.00	32.00	50.00	33,600.00
Packaging Unit Inside	10	0.42	5.00	35.00	35.00	6,125.00
Packaging Unit Single	1	0.04	1.30	21.00	11.50	312.74
Net single without Packaging	1	0.03	1.20	12.00	10.00	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)