

# DIGITUS FTTH Fiber Optic Flush Mount Wall Outlet, for SC/LC adapters

DN-93201

EAN 4016032499121



## Fiber Flush Mount Wall-Outlet For SC and LC Adapter

The Wall Outlet is a specialized in-wall termination solution designed to provide a clean, organized interface for fiber connections in residential, commercial, or industrial environments. Installed directly into the wall, the discreet and space-saving solution enables in improving the functionality and appearance of fiber installations. It serves as the final termination point for optical fibers, providing easy and secure access for connecting Optical Network Terminals (ONTs), routers, or other fiber-enabled devices. It typically accommodates industry-standard adapters such as SC, LC, or other types, ensuring compatibility with various fiber optic systems. By enclosing the fiber termination, it minimizes exposure to dust, physical damage, and accidental disconnection. It also helps maintain proper fiber bend radius, which is essential for preserving signal performance and reducing the risk of fiber breakage or degradation. Its robust construction make it a future-proof solution that supports high-speed internet and data services delivered via fiber optic infrastructure.

**Compact fiber termination point designed for FTTH installations, offering a discreet flush-mounted profile for seamless integration into residential or commercial walls. Ideal for delivering high-speed fiber access.**

- Type : FTTH Fiber Flush Mount Wall Outlet
- Application : Indoor Fiber Termination for FTTH
- Mounting Type : Flush (In-Wall) Mounting
- Fiber Type Compatibility : Singlemode (OS2), Multimode (OM3/OM4)
- Adapter Type Compatibility : SC/APC, SC/UPC, LC/APC, LC/UPC
- Number of Ports : 2
- Bend Radius Protection : Minimum 15mm
- Color : White
- IP Rating : IP20 (Indoor Use)
- Material : High-Quality ABS Plastic
- Dimensions (HxWxD) : 86mm x 86mm x 30mm
- Operating Temperature : -10°C to +60°C
- Storage Temperature : -20°C to +60°C

## Package contents

- 1 x Fiber Optic Flush Mount Wall Outlet
- Screws
- Mounting Bracket
- Instruction Manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	60	9.70	27.20	34.00	39.00	36,067.20
Packaging Unit Inside	1	0.16	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.16	9.00	8.50	9.50	726.75
Net single without Packaging	1	0.12	7.70	8.00	8.00	0.00

**More images:**



**Safety notes**

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)