

# Digitus® DIGITUS USB 3.0 hard disk enclosure, 3.5", SATA, 16TB, aluminum

DA-71106-1

EAN 4016032501343



## SSD/HDD SATA Enclosure 3.5 Zoll USB3.0, for SATA III HDD 3.5 Zoll

The DA-71106-1 hard disk enclosure offers a powerful storage solution for all your requirements. With support for 2.5" and 3.5" SATA hard disk drives and a capacity of up to 16 TB, it enables reliable backup and management of large amounts of data. Thanks to the USB 3.0 interface and the fast transfer rate of up to 5 Gbit/s, files can be transferred quickly and efficiently. This robust and stylish enclosure supports both 2.5" and 3.5" SATA hard drives, accommodates hard drives up to 16TB and ensures smooth performance. The robust aluminum construction ensures long-lasting use and effective heat dissipation. The LED indicator shows operating status and data transfers, while the convenient on/off switch allows for easy operation. Compatible with Windows, macOS and Linux, the enclosure offers versatility. The DA-71106-1 is ideal for home and office use, whether for data backup or mobile storage solutions.

**The DA-71106-1 hard disk enclosure will be your preferred solution for high capacity and high speed external storage.**

- Internal connection: SATA III (compatible with SATA I/II)

- External connection: USB 3.0 (downwards compatible with USB 2.0/1.1)
- Max. supported capacity: 16 TB
- Chipset: JMS578
- LED display: White during operation, flashing during data transmission
- Material: All-aluminum housing
- Operating temperature: 0 to 40 °C
- Storage temperature: -40 to 70 °C
- Humidity: 10 % to 90 % (operation, non-condensing)
- Dimensions: 182 x 113 x 35 mm

## Package contents

- External hard disk enclosure DA-71106-1
- USB 3.0 data cable (A-B, 100 cm, black)
- Power supply unit (12V/2A)
- QIG
- Rubber feet for a secure stand
- Screwdriver and screw package

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
<b>Packaging Unit Carton</b>	30	21.00	40.00	45.00	22.00	39,600.00
<b>Packaging Unit Inside</b>	1	0.70	0.00	0.00	0.00	0.00
<b>Packaging Unit Single</b>	1	0.70	19.40	20.00	6.00	2,328.00
<b>Net single without Packaging</b>	1	0.70	11.50	18.40	3.50	0.00

**More images:**



**Safety notes**

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH

Auf dem Schüffel 3

Lüdenscheid, Germany

<https://www.assmann.com>

info@assmann.com