

DIGITUS® Basis IT PDU, single-phase 32 A, 24 x C13, 2 x C19, 4 x grounded outlets, 3 m power cord, IEC 60309 32 A plug

DN-95453

EAN 4016032508373



IT BASIC PDU, Vertical, 1Ph 32A, 24 x C13, 2 x C19 4 x Safety Outlet, 3m cable, 32A plug

DIGITUS® power strips are the perfect solution for your network or server cabinet. In terms of power distribution, the PDU meets the requirements of many applications in IT, networking, and laboratories. The individual C13 and C19 outlets are equipped with a pull-out protection feature. It is designed for vertical installation, which saves rack units and provides more space for additional devices. The power strip with 30 outlets has excellent physical characteristics and is rated for up to 8,000 W (250 VAC / 32 A), ensuring optimal performance under appropriate load conditions.

A safe and professional power distribution solution for demanding IT requirements in network and server cabinets

- Pull-out protection on every outlet (for C13 and C19 standard cables)
- Vertical Installation
- Housing: Aluminum profile
- Plastic components made of ABS UL-94V-0
- Integrated circuit breakers, 2 x 16 A
- Power cord: 4 mm², IEC 60309 32 A plug

- Power cord: 3 m
- Max. load: 8000 W / 230–250 V AC / 32 A (50/60 Hz)
- Outlets: 24 x C13 outlets, 2 x C19 outlets, 4 x 7/3 outlets
- Output current: C13 (10A), C19 (16A), grounded outlet (16A)
- Dimensions (L x W x D): 1388.5 x 45 x 60 mm
- Color: Black

Attributes

- Additional Features: Circuit breaker
- Current: 32 A
- Input Plug: IEC 60309 32A 1ph/N/PE 6h
- Installation: Rack OU
- Outlets: IEC 60320 C13, IEC 60320 C19, CEE 7/3
- Phase: 1ph
- Power: 7,3 kVA
- Volts: 230 V

Package contents

- 1 power strip
- 1 Safety Instructions

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	4	17.65	23.50	43.50	162.50	166,116.00
Packaging Unit Inside	1	4.41	0.00	0.00	0.00	0.00
Packaging Unit Single	1	4.41	10.00	21.00	160.00	33,600.00
Net single without Packaging	1	3.15	6.00	4.50	150.00	0.00

More images:



Safety notes

- This product is not intended for unsupervised use by children or persons under their care!
- Prevent higher humidity or temperatures than those specified in the data sheet - Avoid moisture, dust or vapors, solvents, flammable gases.
- Multiple sockets are not designed for permanent use with heavy loads!
- Multiple sockets must not be cascaded (avoid stringing together several multiple sockets).
- The maximum connected load must not be exceeded.
- Defective multiple sockets must be taken out of service immediately and disposed of in an environmentally friendly manner.
- In the event of a fault, take the product out of operation and contact a qualified electrician.
- Do not open the product.
- Disconnect the product from the power supply before cleaning. Do not use any aggressive or abrasive cleaning agents for cleaning.
- The ingress of liquids can lead to a short circuit.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com