DIGITUS® Gigabit Ethernet PoE Switch, 8-Port PoE+, 10", up to 80 W PoE budget

DN-95317-1

EAN 4016032509745



Gigabit Ethernet PoE switch 8-port PoE, 10 inch, 80W PoE budget

The DIGITUS® DN-95317-1 reliably supplies PoE-enabled network devices with power and data via eight Gigabit RJ45 ports—all through a single network cable. Thanks to IEEE 802.3af/at (PoE+), it delivers up to 30 W per port and powers access points, IP cameras, VoIP phones, or IoT systems directly, without the need for separate power supplies at the end devices. The total 80-W PoE budget is sufficient for the simultaneous operation of multiple power-hungry devices. The non-blocking store-and-forward architecture ensures lossless Gigabit forwarding without any configuration effort. The fanless metal housing operates silently—ideal for compact 10-inch cabinets and wall-mounted distribution panels in offices, retail settings, residential complexes, or equipment rooms.

Centralized power and gigabit data delivery to PoE-enabled devices via a single cable—ideal for camera systems, Wi-Fi access points, and IP building automation.

- Network & Performance
- 8× 10/100/1000 Mbps RJ45 (PoE+)
- PoE Standards: IEEE 802.3af/at
- Max. 30 W per port, 80 W total PoE budget
- Switching capacity: 16 Gbps, non-blocking
- Total PoE budget: 90 W
- Store-and-Forward, Auto-Negotiation, Auto-MDI/MDI-X
- Non-Blocking Gigabit Switching
- Gigabit speed per port
- Optimized for IP cameras, Wi-Fi access points, and IoT
- Design & Installation
- Completely fanless
- Metal housing
- 10-inch rack mount
- Dimensions: approx. 250 × 150 × 42 mm
- Electrical Systems & Environment
- Internal power supply, 100–240 V AC
- Total power consumption depends on the PoE load (max. approx. 96 W)
- Operating temperature: 0–40 °C; storage temperature: –10–70 °C
- Humidity: 5–95%, non-condensing

Attributes

- Broj priključaka: 8
- PoE norma: IEEE802.3at (PoE+)
- PoE potrošnja energije: 80 W
- Ethernet brzina: Gigabit
- Industrijska uporaba: Ne
- Broj priključaka (Uplink): 8
- PoE (napajanje preko Etherneta): Ne
- Prikladno za vanjsku primjenu: Ne
- Upravljano: Ne
- Veza uzlaznog (Uplink) priključka: RJ45
- VLAN: Ne
- Vrsta instalacije: 10 inča
- Zaštita od vandalizma: Ne

Package contents

- DN-95317-1 Switch
- Power cable
- Quick Start Guide
- Rubber feet

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	8	13.23	26.50	33.00	49.00	42,850.50
Packaging Unit Inside	1	1.65	32.00	24.00	6.70	5,145.60
Packaging Unit Single	1	1.65	32.00	24.00	6.70	5,145.60
Net single without Packaging	1	1.11	25.00	15.00	4.20	0.00

More images:











Safety notes

- This product is intended for indoor use only.
- Read all instructions and follow all warnings and instructions on the device.
- Do not place this appliance on an unstable surface (such as a trolley, stand, table, etc.).
- Do not use this appliance near water.
- Do not place this appliance near or above a radiator.
- The housing is equipped with openings for heat dissipation and ventilation. To prevent overheating during operation, the ventilation openings must not be blocked or covered.
- Do not place the appliance on a soft surface (e.g. bed, sofa, blanket, etc.). This will block the ventilation.
- The appliance must not be installed in a closed environment if adequate ventilation is not guaranteed.
- Do not spray any liquids onto the appliance.
- Disconnect the mains plug before cleaning. Do not use any liquid or foam cleaners.
- Clean the appliance with a damp cloth.
- Connect the device according to the power supply on the rating plate.
- To prevent damage to the appliance, it is important that all appliances are properly earthed.
- Do not place any objects on the power cable and lay it in such a way as to avoid tripping hazards.
- Use a surge protector, a regulator or an uninterruptible power supply (UPS) to protect your system from sudden, temporary and reduced power.
- Secure the system cable and mains cable properly and ensure that no objects are pressing on the cable.
- Do not insert any objects into the appliance through the openings in the housing. There is a risk of a short circuit, which can lead to fire or electric shock.
- Do not attempt to repair the appliance yourself. Always contact an authorized customer service centre.
- If any of the following conditions occur, unplug the appliance and send it to an authorized service centre for repair
- The mains cable, power supply unit or plug for the power supply is damaged or worn;
- Liquid has penetrated the appliance;
- The device has been exposed to rain or water;
- The device has been dropped or the housing has been damaged;
- The function of the device has obviously changed;
- The appliance cannot be operated as described in the operating instructions.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com