

Ubiquiti UBNT TOUGH Cable CARRIER

UB-TOUGH-CABLE-CARRI
EAN 0810354021336



Category 5e outdoor carrier-class shielded cable that features an Anti-Crosstalk Divider, additional shielding and is rated to provide optimal performance on Gigabit Ethernet networks.

- Cable CAT5e, Shielded
- Ethernet Support Up to 1 Gbps
- Conductor Wire Gauge 24 AWG
- Conductor Solid Bare Copper
- Conductor Diameter 0.500 ± 0.005 mm
- Insulation Type Solid PE
- Insulation Thickness AVG: 0.295 mm, MIN: 0.29 mm
- Insulation Diameter 1.16 ± 0.02 mm

- Separation (Polyester Wrapping) Thick: 0.025 mm, Extent: 20 mm
- Anti-Crosstalk Divider LDPE: 4.2×0.3 mm
- Cable Shield (Aluminum Foil) Thick: 0.060 mm, Extent: 20 mm
- ESD Drain Wire 0.4 TC
- Rip Cord Yes
- Secondary Cable Shield (Braid) $16 \times 8 \times 0.16$ AA Density: 95%
- Jacket Material PE
- Jacket Thickness AVG: 0.52 mm, MIN: 0.46 mm
- Jacket Outer Diameter 6.8 ± 0.30 mm
- Jacket Color Gray
- Reference Standard ISO/IEC 11801, TIA/EIA568B.2

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	17.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	12.65	0.00	0.00	0.00	0.00