

Ubiquiti Ubiquiti Networks UniFi Cloud Key Gen2 Plus

UB-CK-G2-PLUS
EAN 0817882024532





The Ubiquiti UniFi CloudKey Gen2 Plus is an integrated hardware controller and self-contained application server designed to monitor and manage your UniFi network devices and camera surveillance system. It features an eight-core processor with 3 GB RAM, a 1 TB SATA HDD for video storage, and 32 GB eMMC flash storage, and utilises the latest version of the UniFi Controller with hybrid cloud technology. Ubiquiti UniFi CloudKey Gen2 Plus Key Features Includes UniFi Protect video surveillance software Includes UniFi SDN network management software Easy setup with UniFi and UniFi Protect mobile apps Powered by 802.3af PoE or QC 2.0 USB-C Built-in battery for automatic safe shutdown 1 TB 2.5" hard drive included (upgradeable to 5 TB) User upgradeable 1TB 2.5" hard drive included Front panel display for at-a-glance system details Hybrid Cloud Technology The Ubiquiti® hybrid cloud configuration provides a secure, private SSO (Single Sign-On) to access all of your UniFi deployments from anywhere in the world. With the Ubiquiti hybrid cloud, a third-party hosted cloud service is not required, so all of your personal data and network information remains local and secure—the way it should be. Incredible, Agile Scalability Add, provision, configure, monitor, and manage all of your UniFi devices, whether in one or hundreds of private networks—all from a centralised control panel. Easily accessible through one of our downloadable apps or a standard web browser (Chrome recommended), the UniFi Cloud Key Gen2 Plus is a powerful solution for managing your UniFi networks across the campus or

across the globe.

- Dimensions: 131.16 x 27.10 x 134.20 mm (5.16 x 1.07 x 5.28")
- Weight: 582 g (1.28 lb)
- Enclosure: Anodised Aluminum
- Management Interface: UniFi Management Portal; UniFi SDN; UniFi Protect
- Hard Drive Capacity: 1 TB 2.5" SATA HDD (user-upgradeable)
- Device Capacity:
- UniFi Protect Mode: Up to 20 UniFi Cameras
- UniFi SDN + UniFi Protect: Up to 15 UniFi Cameras and 50 UniFi Devices
- Processor: APQ8053 8 Core with 3 GB RAM
- eMMC Memory: 32 GB
- Networking Interface: 1 x 10/100/1000 Ethernet Port
- Buttons: 1 x Power; 1 x Reset
- LEDs: 1 x Power, White/Blue
- Power Method: Standard 802.3af PoE; Quick Charge 2.0/3.0 Power Adapter (9VDC, 2A)
- Supported Voltage Range: Standard 802.3af PoE or 9VDC, 2A
- Maximum Power Consumption: 12.95W (PoE); USB-C Power
- Operating Temperature: 0 to 35° C (32 to 104° F)
- Operating Humidity: 20 to 80% Noncondensing
- Certifications: CE, FCC, IC

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	0.60	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.60	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.60	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:



EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

Discomp s.r.o
Dopravní 1218/2a
Plzeň, Czech Republic
<https://www.discomp.cz/>
info@discomp.cz