

# TP-Link VIGI solar system controller without solar panel

VIGI PS90  
EAN 1210002601009



VIGI solar system controller without solar panel Specification: Up to 3 × 31.2Ah/3\*12VDC output battery, more than 500 cycles; State of charge: -20°C~45°C (with intelligent auxiliary heating); Discharge condition: -30°C~60°C (with intelligent auxiliary heating); 1\*10/100Mbps RJ45 Function: Load Control\Battery Over Temperature Protection\Battery Level Indicator\Generation Power Display\Load Power Display\Generation Power Display and Load Power Statistics.

## VIGI Solar System Controller

- Battery capacity: 93.6 Ah (max), 31.2 Ah (per lithium battery)
- 1× Three-pin female connection to connect the controller
- 1× Three-pin male plug to connect the modular battery
- 2× Four-pin female connectors to connect the solar panel

- 1× 10/100 Mbps RJ45
- 3× 5.5mm DC Plug (#1, #2: 9V-12.6VDC/2A, #3: 12VDC/2A)
- Operating temperature: -30°C-60°C (with intelligent auxiliary heating)
- Operating humidity: 10% ~90% RH, non-condensing

## Package contents

- VIGI PS90
- Quick Start Guide
- Waterproof Cable Fasteners
- Mounting accessories
- Extension cable
- Boxing key

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

## More images:





**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

TP-Link Deutschland GmbH  
Am Trippelsberg 100  
Düsseldorf, Germany  
<https://www.tp-link.com/de/>  
[support.de@tp-link.com](mailto:support.de@tp-link.com)