

TP-Link Omada 5G/4G Outdoor Gateway

ER701-5G-OUTDOOR
EAN 1210002601405



Omada 5G Outdoor Gateway CONNECTOR: 1x2.5 GB PoE-in port, 2 nano SIM slots SPEED: SA: Downlink: 7.01 Gbps, Uplink: 1.25 Gbps; NSA: Downlink: 4.5 Gbit/s, Uplink: 730 Mbit/s. 150 Mbps Wi-Fi speed (for setup only) Function: Integration with Omada SDN Controller, 9x internal cellular antennas + 1x internal Wi-Fi antenna (for easy setup), 5G support, app-guided antenna alignment for optimal 5G performance, support router mode and IP passthrough mode, policy-based firewall, static routing, policy routing, multi-net DHCP, VLAN, stateful ACL, bridge VLAN, IP66, 183*110*36mm

Omada 5G Outdoor Gateway

- 5G
 NR:N1/N3/N5/N7/N8/N20/N26/N28/N38/N40/N41/N75/N76/N77/N78
 (2100/1800/850/2600/900/800/850/700/2600/2300/2500/1500/1450/3700/3500 MHz)

- 4G FDD-LTE: B1/B3/B5/B7/B8/B20/B26/B28/B32 (2100/1800/850/2600/900/800/850/700/1500MHz)
- 4G TDD-LTE: B38/B40/B41/B42/B43 (2600/2300/2500/3500/3700)MHz
- 3G WCDMA: B1/B5/B8 (2100/850/900MHz)
- Interface: 1x2.5G RJ45 port
- Power Supply: 802.3at PoE: 42-57V 0.6A / Passive PoE: 48V 0.375A
- Operating Temperature: -30°C to 60°C (-22°F to 140°F)
- Storage Temperature: -40°F to 158°F (-40°C to 70°C)

Package contents

- ER701-5G-Outdoor
- Quick Start Guide
- Waterproof kit
- Mounting kit
- Passive PoE Adapter

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	8	6.16	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	1.75

More images:



EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

TP-Link Deutschland GmbH
Am Trippelsberg 100
Düsseldorf, Germany
<https://www.tp-link.com/de/>
support.de@tp-link.com