

TP-Link Omada Hardware Controller

OC220

EAN 1210002602457



Omada Hardware Controller PORT: 2x 10/100/1000Mbps Ethernet ports, 1x USB 2.0 port, 1x Micro USB port FEATURE: Cloud access, centralized management of up to 100 Omada EAPs + 20 Omada switches + 10 Omada gateways, powered by 802.3af/at PoE or Micro USB power adapter, Omada app, metal case

Omada Hardware Controller

- 2x Gigabit Ethernet ports
- 1x USB 2.0 port

- 1x Micro USB port
- Power Supply: 802.3af PoE; Micro USB (DC 5V/minimum 1A)
- Operating temperature: -5-50 °C (23-122 °F)
- Storage Temperature: -40-70°C (-40-158°F)

Package contents

- OC220
- Short installation guide
- RJ45 Ethernet Cable

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	40	18.40	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:





EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

TP-Link Deutschland GmbH
Am Trippelsberg 100
Düsseldorf, Germany
<https://www.tp-link.com/de/>
support.de@tp-link.com