

# DIGITUS Wall Mounting Cabinet Unique Series - double sectioned, pivoted

DN-19-20U-3-1  
EAN 4016032190820



## 20U wall mounting cabinet, Unique, 998x600x600 mm double sectioned, pivotable, grey (RAL 7035)

The network cabinets for wall installation from the Unique series were developed for especially convenient and flexible network cabling. Thanks to the integrated hinge in the back frame, the housing can be folded to the side if needed, for example in order to easily carry out assembly work in the back area of the cabinet. There is a sliding cable inlet with foam rubber seal in the roof of each cabinet. The back wall and floor plate are equipped with pre-cut cable inlets with a plastic cover. In addition, the back frame is equipped with brush management panels on the top and bottom. To accommodate a fan module, the roof structure is also equipped with a pre-cut area. One pair of galvanized 483 mm (19") profile rails labeled with rack units readable in both directions are installed on the inside. Their depth can be adjusted. The back frame also has a 483 mm (19") perforation. Each cabinet is made of up to 1.5 mm thick sheet steel. Coloring is done with electrostatic powder coating in the standard colors gray (RAL 7035) or jet black (RAL 9005). Removable and lockable side walls in a modular design as well as lockable and removable front door improve accessibility. The door hinges can be switched. Wall installation is accomplished in two easy work steps: The housing frame plate is bolted on the wall to open in either direction and then connected with the housing. With optionally available levelling feet or casters, the wall housings from the Unique series can also be used as a free-standing unit.

**The DIGITUS® Unique Series is made for high demand IT-Infrastructure Solutions - designed and developed on highest standard in Germany**

- Safety class rating IP20
- Lockable safety-glass door with steel frame
- 210° door opening angle
- Housing is connected to rear frame with separate locking mechanism (incl. individual key)

- 102° pivotable angle of the housing from the frame
- 1-point-locking-mechanism on the front door
- Side panels are lockable and removable
- 483 mm (19") profile rails mounted on the front side inside of the cabinet, galvanized
- 483 mm (19") profile rails are adjustable in depth and with height unit marking
- Rear frame with 483 mm (19") punch outs
- Max. installation depth: 440 mm
- Cable entry on the rear side and base with plastic cover and top with sliding cover
- Rear frame with brush strip for cable entry on top and base
- Roof is prepared for fan units (punched out entries)
- Ventilation slots for active and passive ventilation and exhausting
- Ventilation slots for active and passive ventilation and exhausting
- Several earthing points for rack components
- Incl. installation set (screws, cage nuts, washers)
- Rack is completely mounted
- Equipment mounting depth min.-max.: 375-440 mm
- Cabinet type: Wall mounting cabinet
- Color: light grey, RAL 7035
- Depth: 600 mm
- Front door: Glass door, single opening
- Load capacity: 80 kg
- Side panels: Both sides
- Units: 20
- Width: 600 mm
- IP protection class: IP20
- Mounted: yes

### Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- 2 x Keys

| Logistics                    |              |             |            |            |             |        |
|------------------------------|--------------|-------------|------------|------------|-------------|--------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³    |
| Packaging Unit Carton        | 2            | 58.50       | 65.00      | 65.00      | 104.80      | 442.80 |
| Packaging Unit Inside        | 1            | 58.50       | 65.00      | 65.00      | 104.80      | 442.80 |
| Packaging Unit Single        | 1            | 58.00       | 65.00      | 65.00      | 104.80      | 442.80 |
| Net single without Packaging | 0            | 53.00       | 60.00      | 60.00      | 99.80       | 359.30 |

**More images:**

