

DIGITUS CAT 5e U/UTP patch cord

DK-1512-100
EAN 4016032198772



CAT 5e U-UTP patch cord, PVC AWG 26/7, length 10 m, color grey

The DIGITUS® Category 5e Class D patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 5e specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 5e cabling. The performance is tested up to 100 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 5e, because of the transparent blue colored connector.

Future-oriented standards and high-end quality for your network.

- 2x RJ45 (8P8C) connectors
- Boots with kink protection, strain relief and latch protection
- Length marking on boot
- Assortment: Twisted Pair Patch Cables
- Configuration: 1:1
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Packaging: DIGITUS Polybag
- Category: CAT 5e
- Shielding: U-UTP, unshielded
- Length: 10 m
- Color: grey
- Jacket: PVC
- Slim Version: no
- Structure: 4 x 2 AWG 26/7, twisted pair

Logistics

| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
|------------------------------|--------------|-------------|------------|------------|-------------|----------|
| Packaging Unit Carton | 45 | 8.50 | 36.00 | 36.00 | 27.00 | 35.00 |
| Packaging Unit Inside | 5 | 0.94 | 25.00 | 25.00 | 34.00 | 21.30 |
| Packaging Unit Single | 5 | 0.22 | 5.00 | 19.00 | 27.00 | 2.60 |
| Net single without Packaging | 0 | 0.22 | 1.00 | 1.20 | 1.30 | 1,485.90 |

More images:



