

DIGITUS® USB-A - USB-B connection cable, 1.8m

AK-300102-018-S
EAN 4016032284789



USB connection cable, type A - B M/M, 1.8m, USB 2.0 suitable, bl

For connecting external USB end devices (with B socket, e.g. external hard disk enclosures, scanners or printers) to the USB host (e.g. PC, notebook or USB hub). Transfer rate up to 480 Mbps (high-speed).

Secure and reliable connection



Attributes

- Assortment: USB Cables

- Color cable: black
- Color connector: black
- Connector 1: USB A, plug
- Connector 2: USB B, plug
- Connector surface: nickel-plated
- Ferrite filter: none
- Hoods: molded
- USB compliance: USB 2.0
- Length: 1.8 m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	320	15.00	32.00	45.00	25.00	36.00
Packaging Unit Inside	1	0.05	32.00	16.00	4.00	2.05
Packaging Unit Single	1	0.05	0.70	11.50	21.00	169.05
Net single without Packaging	0	0.04	1.00	11.00	10.00	110.00

More images:





Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com