

DIGITUS® Fast Ethernet Media Converter, RJ45 / SC

DN-82021-1

EAN 4016032293101



Fast Ethernet Media Converter, Singlemode SC connector, 1310nm, up to 20km

The Media Converters from DIGITUS are the ideal solution for the migration of Copper and Fiber Network Signals. From now on, you are able to access the Fiber Technology and transfer network signals over several kilometers without renewing your whole Network Infrastructure. The huge variety of Products fulfil your individual needs. The intuitive operation guarantees a quick and easy Installation. The Link Fault Pass Through function offers a no-fear-networking. Your Network Administrator will be able to find and solve Network problems easily. Years of Experience and a wide range of products lets DIGITUS become a reliable Partner for your Network.

The perfect converter solution for various fiber media

- Transforms wire based network media to fiber optic
- High quality and excellent reliability
- 10/100Base-TX to 100Base-FX
- Connectors: 1x RJ45, 1x SC duplex
- Distance up to 20km
- Wavelength: 1310nm
- Singlemode Dual Fiber
- Automatic cable detection - auto MDI / MDI-X function
- Auto-negotiation of full- and half-duplex
- Diagnostic and monitoring LEDs for the status of power, link and act of the ports
- Link Fault Pass Through (LFP) function for easier network maintenance
- Suitable for 9/125µm Fiber Cables

- Transmission Power: Minimum -15 dBm, Maximum -8 dBm
- Sensitivity Receiving Power: Minimum -38 dBm
- Supported Standards: IEEE 802.3 Ethernet, IEEE 802.3u Fast Ethernet
- 128kB data buffer
- Operating temperature: 0 to 55°C
- Dimensions (L x W x H): 95mm x 70mm x 26mm
- Weight: 200g
- Standalone Converter with external power supply
- Input Supply Voltage: 5V DC
- Max. Current: 800mA
- Power Consumption: 2.5W

Attributes

- Connector 1: RJ45
- Connector 2: SC
- Mode: Singlemode
- Distance (km): 20
- Industrial usage: no
- Broadcasting Mode: Unidirectional
- PoE injector: no
- Ethernet speed: Fast Ethernet

Package contents

- Media Converter
- Quick installation guide
- Power adapter

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	9.00	30.00	27.00	55.00	44.55
Packaging Unit Inside	1	0.45	6.00	21.60	16.10	2,086.56
Packaging Unit Single	1	0.45	6.00	21.60	16.10	2,086.56
Net single without Packaging	0	0.18	12.00	7.00	2.60	218.40

More images:



Model Name	Serial	Contract	Release	Medium	WaveLength	Operating Temperature	PowerSource
DM-4000-01	4000000001	1000000001	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-02	4000000002	1000000002	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-03	4000000003	1000000003	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-04	4000000004	1000000004	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-05	4000000005	1000000005	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-06	4000000006	1000000006	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-07	4000000007	1000000007	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-08	4000000008	1000000008	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-09	4000000009	1000000009	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-10	4000000010	1000000010	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-11	4000000011	1000000011	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-12	4000000012	1000000012	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-13	4000000013	1000000013	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-14	4000000014	1000000014	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-15	4000000015	1000000015	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-16	4000000016	1000000016	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-17	4000000017	1000000017	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-18	4000000018	1000000018	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-19	4000000019	1000000019	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-20	4000000020	1000000020	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-21	4000000021	1000000021	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-22	4000000022	1000000022	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-23	4000000023	1000000023	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-24	4000000024	1000000024	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-25	4000000025	1000000025	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-26	4000000026	1000000026	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-27	4000000027	1000000027	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-28	4000000028	1000000028	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-29	4000000029	1000000029	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-30	4000000030	1000000030	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-31	4000000031	1000000031	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-32	4000000032	1000000032	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-33	4000000033	1000000033	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-34	4000000034	1000000034	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-35	4000000035	1000000035	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-36	4000000036	1000000036	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-37	4000000037	1000000037	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-38	4000000038	1000000038	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-39	4000000039	1000000039	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-40	4000000040	1000000040	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-41	4000000041	1000000041	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-42	4000000042	1000000042	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-43	4000000043	1000000043	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-44	4000000044	1000000044	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-45	4000000045	1000000045	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-46	4000000046	1000000046	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-47	4000000047	1000000047	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-48	4000000048	1000000048	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-49	4000000049	1000000049	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-50	4000000050	1000000050	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-51	4000000051	1000000051	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-52	4000000052	1000000052	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-53	4000000053	1000000053	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-54	4000000054	1000000054	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-55	4000000055	1000000055	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-56	4000000056	1000000056	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-57	4000000057	1000000057	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-58	4000000058	1000000058	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-59	4000000059	1000000059	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-60	4000000060	1000000060	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-61	4000000061	1000000061	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-62	4000000062	1000000062	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-63	4000000063	1000000063	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-64	4000000064	1000000064	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-65	4000000065	1000000065	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-66	4000000066	1000000066	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-67	4000000067	1000000067	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-68	4000000068	1000000068	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-69	4000000069	1000000069	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-70	4000000070	1000000070	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-71	4000000071	1000000071	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-72	4000000072	1000000072	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-73	4000000073	1000000073	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-74	4000000074	1000000074	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-75	4000000075	1000000075	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-76	4000000076	1000000076	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-77	4000000077	1000000077	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-78	4000000078	1000000078	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-79	4000000079	1000000079	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-80	4000000080	1000000080	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-81	4000000081	1000000081	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-82	4000000082	1000000082	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-83	4000000083	1000000083	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-84	4000000084	1000000084	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-85	4000000085	1000000085	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-86	4000000086	1000000086	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-87	4000000087	1000000087	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-88	4000000088	1000000088	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-89	4000000089	1000000089	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-90	4000000090	1000000090	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-91	4000000091	1000000091	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-92	4000000092	1000000092	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-93	4000000093	1000000093	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-94	4000000094	1000000094	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-95	4000000095	1000000095	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-96	4000000096	1000000096	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-97	4000000097	1000000097	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-98	4000000098	1000000098	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-99	4000000099	1000000099	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC
DM-4000-100	4000000100	1000000100	10/10/2008	10/100Mbps	1310nm	0°C to 40°C	DC

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com