DIGITUS DVI extension cable

AK-320200-100-S EAN 4016032298502





• [::::::]



DVI extension cable, DVI(24+1), 2x ferrit M/F, 10.0m, DVI-D Dual Link, bl

This digital, Full HD suitable DVI cable (Dual Link), is used to extent existing connections of audio/video equipment or cables with DVI(24+1) interface, such as between PC, notebook, monitor, TV or a projector, for example.

Full HD, Dual-Link

- Support up to 2560 x 1600 pixel with 30Hz
- DVI-D (24+1) plug <=> DVI-D (24+1) jack
- Molded housing
- Cable full connected, double shielded, AWG28
- 2x ferrite filter
- UL20276
- Color: Black

Attributes

Assortment: DVI Cables

- AWG: 30
- Color cable: black
- Color connector: black
- Connector 1: DVI-D, (24+1), plugConnector 2: DVI-D, (24+1), jack
- Connector surface: nickel-plated
- Ferrite filter: 2 x ferrite beads
- HDTV Resolution max.: 2560 x 1600 Pixel, 60Hz
- HDTV Resolution max.: 2560 x 1600 Fixel, 60F
 HDTV Standard: Full HD
- Hoods: molded
- Packaging: Polybag
- Wire material: CU
- Length: 10 m
- Shielding: Double shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	10.10	39.00	31.00	21.00	25.39
Packaging Unit Inside	1	1.01	19.00	22.00	6.00	2.51
Packaging Unit Single	1	1.01	17.00	19.00	4.00	1.29
Net single without Packaging	0	1.01	17.00	19.00	4.00	1.29

Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- · Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum
 operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.



EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com