

# DIGITUS® Gigabit Ethernet PCI Network Card

DN-10110

EAN 4016032310778



**Gigabit Ethernet PCI Card 32-bit, low profile bracket, RTL8169SC chipset**

Gigabit Ethernet PCI Card, 32-bit, low profile bracket, RTL8169SC chipset

**Unprecedented speed is now available over your existing network cabling - Built to run the fastest network applications**

- Supports 10/100/1.000 Mbps auto negotiation
- IEEE 802.3, IEEE 802.3u, IEEE 802.3ab compatible
- IEEE 802.3x full-duplex and flow control
- Supports Autonegotiation and Crossover detection
- Realtek Chipset
- PCI Local Bus Master Rev.2.1 and 2.2 compatible
- Suitable for all common network environments
- Additional Low Profile Bracket to use the Card also in Thin Computers
- Operating temperature: 0 °C - 70 °C
- Operating humidity: 25% - 65% RH (non-condensing)
- Supports Windows 10, 8.1, 8, 7, Vista, XP, Mac OS X and Linux
- Chipset: Realtek RTL8169SC Gigabit Ethernet Controller

- Bus: PCI V2.2, 32/64-bit, 33/66MHz
- IEEE802.3, IEEE802.3u, and IEEE802.3ab compliant.
- Support for IEEE802.3x Full-Duplex flow control
- Support IEEE802.1Q Virtual LAN (VLAN) Tag
- Complaint to PC97, PC98, PC99 and PC2001 standards
- Auto-Negotiation support for Auto-Detect 10/100/1000Mbps data rate and Full/Half-Duplex operation mode
- Support ACPI and PCI power management
- Automatic crossover support for crossover or regular cable
- Support Boot ROM function (optional)
- Support Wake on LAN function
- One RJ-45 Port

**Package contents**

- Gigabit Ethernet PCI network card
- Low profile bracket
- Quick installation guide
- Product support CD-ROM

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	40	6.30	38.00	41.00	41.00	63.88
Packaging Unit Inside	1	0.16	5.50	18.00	18.60	1,841.40
Packaging Unit Single	1	0.16	5.50	18.00	18.60	1,841.40
Net single without Packaging	0	0.05	12.10	11.50	1.90	264.39

**More images:**



**Safety notes**

- Switch off the computer completely and disconnect it from the power supply before installing or removing the network card.
- Static discharge can damage the product or the PC. Take measures against static discharge (ESD) when installing the product, e.g. wear an antistatic wrist strap.
- Before installation, touch the metal surface of the PC housing or another grounded object to ground any ESD charge via the housing.
- Avoid using too much force when connecting the product to the PC.
- Please ensure that any cables are connected correctly without overstretching or damaging them.
- Avoid touching the contacts of the product with your fingers to prevent corrosion or static charge.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)