

# DIGITUS VGA Splitter 500MHz, 4-Port

DS-42110

EAN 4016032323815



## Video Splitter 1 PC, 4 Monitors 500 MHz, HDSUB 15/F - 4xHDSUB 15/F, Max. 2048x1536p

With a video splitter you can use one video source to display identical images on 2, 4, 8, or 16 monitors - or on even more screens by means of cascading. Thus, a video splitter can be used in various application fields, e.g. test bench facilities, data centers, help desks, video broadcasting, presentations and educational facilities.

### Provides simultaneous display on four different monitors - Perfect for classrooms, tradeshow, or in-store displays!

- Enables to split a video-signal from a PC onto 4 monitors, or other video output devices
- Video bandwidth: 500MHz
- Max. resolution: 2048x1536p @60Hz
- Max. transmission distance: 75m

- Cascadable (max. 64)
- Metal housing for better EMI shielding
- DDC, DDC2, DDC2B support
- Video IN/OUT: HD DSUB, 15-pin, jacks
- HDTV Resolution max.: 2048 x 1536 Pixel, 60Hz
- HDTV Standard: Full HD
- Number of ports: 4
- Signal input: VGA
- Signal output: VGA

### Package contents

- VGA splitter 500MHz, 4-port
- Power supply
- Manual

## Logistics

|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³   |
|------------------------------|--------------|-------------|------------|------------|-------------|-------|
| Packaging Unit Carton        | 10           | 7.50        | 32.00      | 27.00      | 32.50       | 28.10 |
| Packaging Unit Inside        | 1            | 0.75        | 6.00       | 25.00      | 15.00       | 2.30  |
| Packaging Unit Single        | 1            | 0.75        | 6.00       | 25.00      | 15.00       | 2.30  |
| Net single without Packaging | 0            | 0.75        | 0.00       | 0.00       | 0.00        | 0.00  |

## More images:



