

DIGITUS DisplayPort adapter cable

AK-340306-020-S
EAN 4016032328537



DisplayPort Adapter Cable, Type DP-DVI (24+1) M/M, 2.0m, w/interlock, DP 1.1a comp., bl

This digital HD cable converts DisplayPort signals into DVI signals and is ideal for connecting devices with a DisplayPort interface to an HD-compatible TV, projector or monitor with a DVI interface.

Connect a DVI-capable monitor to a DisplayPort video card/source

- Supports up to 1080p with 60 Hz
- Copper cores, foil and braid shielded for robustness and a reliable connection
- Plug and play, no additional driver required
- Supported transmission modes: RBR, HBR, HBR2
- Maximum bandwidth: 10.8 Gbps
- HBR version/transfer mode: HBR1 (2.70 Gbit/s per lane)
- HDCP version: HDCP 1.3

- OFC solid copper cable (99.9 % oxygen-free)


Attributes

- Assortment: DisplayPort Cables
- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: DVI-D, (24+1), plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.1a
- HDTV Resolution max.: 1920 x 1080 Pixel, 60Hz
- HDTV Standard: Full HD
- Hoods: molded
- Interlock: Snap fastener
- Length: 2 m
- AOC - Active Optical Cable: no

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	50	6.50	28.00	34.00	45.00	42.84
Packaging Unit Inside	1	0.13	22.00	15.00	2.00	660.00
Packaging Unit Single	1	0.13	22.00	15.00	2.00	660.00
Net single without Packaging	0	0.13	22.00	15.00	2.00	660.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com