

DIGITUS® Internal power supply cable

AK-430405-003-M
EAN 4016032382140



Internal Y-power supply cable M/F/F, 0.3m, SATA 15-pin - 2x SATA 15-pin

This cable used for the power distribution of 2 SATA-HDD's over one SATA 15-pin port of the PC power supply.

Safe connection and power supply

- SATA 15-pin, plug <=> 2x SATA 15-pin, jack

Attributes

- Assortment: Internal Power Supply Cables

- AWG: 18
- Color cable: various
- Color connector: black
- Connector 1: SATA 15-pin plug
- Connector 2: 2x SATA 15-pin jack
- Hoods: plastic
- Wire material: CU
- Length: 0.3 m
- Shielding: Unshielded

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	250	5.00	45.00	34.00	28.00	42.84
Packaging Unit Inside	1	0.02	28.00	18.00	4.00	2.02
Packaging Unit Single	1	0.05	19.50	10.00	1.00	195.00
Net single without Packaging	0	0.02	105.00	8.00	1.00	840.00

Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH

Auf dem Schüffel 3

Lüdenscheid, Germany

<https://www.assmann.com>

info@assmann.com