

DIGITUS CAT 6 U/UTP patch cord - LSZH

DK-1617-200
EAN 4016032388173



CAT 6 U-UTP patch cord, Cu, LSZH AWG 26/7, length 20 m, color grey

The DIGITUS® Category 6 Class E patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6 specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 6 cabling. The performance is tested up to 250 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 6, because of the transparent red colored connector.

Future-oriented standards and high-end quality for your network.

- 2x RJ45 (8P8C) connectors
- Boots with kink protection, strain relief and latch protection
- Length marking on boot
- Conductor: Copper (Cu)
- Slim Version: no
- Length: 20 m
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Category: CAT 6
- Packaging: DIGITUS Polybag
- Color: grey
- Configuration: 1:1
- Jacket: LSOH
- Shielding: U-UTP, unshielded
- Structure: 4 x 2 AWG 26/7, twisted pair

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	10.80	33.00	33.00	23.00	25.00
Packaging Unit Inside	5	2.70	22.00	32.00	47.00	33.10
Packaging Unit Single	1	0.63	4.40	23.00	32.00	3,238.40
Net single without Packaging	0	0.63	2.00	1.20	1.30	2,971.80

More images:



