

# DIGITUS® DisplayPort 3in1 Adapter / Converter

AK-340418-002-S  
EAN 4016032433781



**DisplayPort Converter Cable, Type DP-HDMI,DVI,VGA M-F/F/F, 0.2m, 3in1 Multi-Media cable, gold,bl**

This adapter / converter will be used to connect your computer or notebook with DisplayPort interface to any HDMI, DVI or VGA display.

**No need to buy 3 single adapter**

- Converts Displayport signals into HDMI, DVI and VGA signals
- Input: 1x DisplayPort; Output: 1x HDMI & 1x DVI & 1x VGA
- Support 4K/2K with 30Hz
- DisplayPort 1.2 Data rate up to 5.4Gbit/s
- HDMI 1.4 Data rate up to 3Gbit/s
- DVI & VGA interfaces support Full HD 1080P@60Hz
- VGA resolution up to WUXGA 1920x1200 dpi (reduced blanking)
- Plug and Play Installation
- No power supply unit required

**Attributes**

- Assortment: DisplayPort Cables
- AWG: 28/30

- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: DP, jack + HDMI type A, jack + DVI-D, jack
- Connector surface: gold-plated
- DisplayPort standard: DisplayPort 1.2
- Ferrite filter: none
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 0.2 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

**Package contents**

- DisplayPort 3in1 adapter / converter, DP - HDMI+DVI+VGA

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	200	11.80	38.00	30.00	31.00	35.34
Packaging Unit Inside	1	0.20	15.00	20.00	7.00	2.10
Packaging Unit Single	1	0.06	18.00	14.00	2.00	504.00
Net single without Packaging	0	0.05	28.50	4.00	1.60	182.40

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)