

DIGITUS® DisplayPort Adapter Cable, DP - HDMI type A

AK-340303-030-S
EAN 4016032438601



DisplayPort Adapter Cable, Type DP - HDMI A M/M, 3.0m, w/lock, 4K@60Hz, DP 1.2, HDMI 2.0, bi

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with DisplayPort interface to a monitor with HDMI interface.

Avoid the hassle of adapters, with a plug-and-play adapter cable which doesn't require external power

- Support of HDMI 2.0 Features
- Support up to 4K/2K with 60Hz
- Support of 3D with 1080p resolution
- Support of HDCP and DPCP
- Supported transmission modes: RBR, HBR, HBR2
- Maximal bandwidth: 21,6 Gbps
- HBR-Version/transfer mode: HBR2 (5,40 Gbit/s per lane)

Attributes

- Assortment: DisplayPort Cables
- AWG: 28
- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: HDMI type A, plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.2
- Ferrite filter: none
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 3 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	150	10.50	25.00	35.00	55.00	48.13
Packaging Unit Inside	1	0.07	10.00	24.00	38.00	9.12
Packaging Unit Single	1	0.24	3.00	18.00	18.00	972.00
Net single without Packaging	0	0.00	2.00	17.00	17.00	578.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com