# **DIGITUS Modular KVM switch, 8-port**

DS-72213 EAN 4016032447603





### KVM module, 8-port for modularized KVM console

The modular DIGITUS® KVM switch offers a multitude of individual configuration possibilities, so that it can be adjusted to the area in which the console is being used. As a result, the console is economical and can be upgraded and/or converted at any time with further modules. Due to the flexible configuration, a high level of future security of the console is thus guaranteed. The modular KVM switch offers the connection of a server via USB or PS/2, as well as VGA. The DIGITUS® 17" oder 19" modular console, a keyboard and the appropriate set of cables are required for operation. The high quality KVM switch modules with IP function (optional) are ideal for use in small to mid-sized server rooms in which access by the administrator must be guaranteed from any place at any time. They offer a direct connection from a local console or with the optional IP module with a browser via an existing internet connection. The accessories are offered in the most diverse versions.

# Highest degree of flexibility during the administration of the server farm

 Controlling several PCs via the 17" or 19" DIGITUS® modular console

- Remote access via IP with the optional DS-51000-1 IP module
  Full control under all OS, in BIOS level, during boot, or at Blue
- Screens
- No software required
- Remote power wakeup on the target computer
- Extension via cascading possible
- Resolution independent of the installed console
- Hot plug support
- Keyboard and mouse emulation ensuring an error-free boot-up procedure of the computer

1

- Autoscan (5 to 90 sec., selectable)
- Compliant to USB 2.0 specification

# Attributes

Cascading possible: no

### Package contents

- Modular KVM switch, 8-port
- Quick installation guide
- Mounting material
- 8 x Combo KVM cable
- 8 x Combo KVM cable

| Logistics                    |                 |                |               |               |                |          |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|----------|
|                              | Number<br>(pcs) | Weight<br>(kg) | Depth<br>(cm) | Width<br>(cm) | Height<br>(cm) | cm³      |
| Packaging Unit Carton        | 4               | 14.92          | 47.50         | 33.00         | 44.00          | 68.97    |
| Packaging Unit Inside        | 1               | 3.73           | 47.50         | 15.20         | 22.00          | 15.88    |
| Packaging Unit Single        | 1               | 3.73           | 44.50         | 14.80         | 4.50           | 2,963.70 |
| Net single without Packaging | 0               | 3.32           | 44.50         | 14.80         | 4.50           | 2,963.70 |



More images:



## Safety notes

- This product is intended for indoor use only.
- Read all instructions.
- Follow all warnings and instructions on the device.
- Do not place this appliance on an unstable surface (such as a trolley, stand, table, etc.).
- If this appliance falls, it can cause serious damage.
- Do not use this appliance near water. .
- Do not place this appliance near or above a radiator.
- The housing is equipped with openings for heat dissipation and ventilation. To prevent overheating during operation, the ventilation openings must not be blocked or covered.
- Do not place the appliance on a soft surface (e.g. bed, sofa, blanket, etc.). This will block the ventilation.
- The appliance must not be installed in a closed environment if adequate ventilation is not guaranteed.
- Do not spray any liquids onto the appliance.
- Disconnect the mains plug before cleaning. Do not use any liquid or foam cleaners.
- Clean the appliance with a damp cloth.
- Connect the device according to the power supply on the rating plate.
- This device is designed for the IT distribution system with 100 V 230 V voltage.
- To prevent damage to the appliance, it is important that all appliances are properly earthed.
- Do not place any objects on the power cable and lay it in such a way as to avoid tripping hazards.
- If an extension cable is used for the appliance, make sure that the total capacity of all products using the cable does not exceed the current load. •
- Ensure that the total current of all products connected to the socket does not exceed 15 A.
- Use a surge protector, a regulator or an uninterruptible power supply (UPS) to protect your system from sudden, temporary and reduced power. Secure the system cable and mains cable properly and ensure that no objects are pressing on the cable.
- Do not insert any objects into the appliance through the openings in the housing. There is a risk of a short circuit, which can lead to fire or electric shock.
- Do not attempt to repair the appliance yourself. Always contact an authorized customer service centre.
- If any of the following conditions occur, unplug the appliance and send it to an authorized service centre for repair
- The mains cable or plug is damaged or worn;
- Liquid has penetrated the appliance;
- The device has been exposed to rain or water;
- The device has been dropped or the housing has been damaged;
- The function of the device has obviously changed;
- The appliance cannot be operated as described in the operating instructions.

# EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com