

# DIGITUS® Modular Cat.5 KVM switch, 16-port

DS-72217

EAN 4016032447641



### CAT 5 KVM module, 16 port for modularized KVM console

The modular DIGITUS® CAT 5 KVM switch offers a wide range of individual configuration options so that the console can be customised to the area of application. This makes the console cost-effective and allows it to be upgraded or converted with additional modules at any time. The flexible configuration guarantees that the console is highly future-proof. The modular CAT 5 KVM switch offers the connection of up to 16 servers via USB or PS/2 as well as VGA via CAT 5 adapter with a range of up to 60 metres. The DIGITUS® 17" or 19" modular console, keyboard and the corresponding CAT 5 adapter are required for operation. The high-quality CAT 5 KVM switch modules with IP function (optional) are ideal for use in small to medium-sized server rooms where administrator access must be guaranteed at all times from any location. They offer direct connection from a local console or with the optional IP module via an existing Internet connection with a browser. The accessories are available in a wide range of variants.

### Highest degree of flexibility during the administration of the server farm

- Controlling several PCs via the 17" or 19" DIGITUS® modular console
- The use of Cat.5 UTP cables allows a distance of 60 meters between the individual servers and the KVM switch

- Remote access via IP with the optional DS-51000-1 IP module
- Full control under all OS, in BIOS level, during boot, or at Blue Screens
- No software required
- Remote power wakeup on the target computer
- Extension via cascading possible
- Resolution independent of the installed console
- Hot plug support
- Keyboard and mouse emulation ensuring an error-free boot-up procedure of the computer
- Autoscan (5 to 90 sec., selectable)
- Compliant to USB 2.0 specification

### Attributes

- Cascading possible: yes
- Interface: CAT 5
- Number of ports: 16

### Package contents

- Modular CAT 5 KVM switch, 16-port
- Quick start guide
- Mounting material
- 16 x Cat. 5 dongle

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	4	12.60	47.50	33.00	44.00	68.97
Packaging Unit Inside	1	3.15	47.50	15.20	22.00	15.88
Packaging Unit Single	1	3.15	44.50	14.80	4.50	2,963.70
Net single without Packaging	0	3.80	44.50	14.80	4.50	2,963.70

**More images:**



**Safety notes**

- This product is intended for indoor use only.
- Read all instructions.
- Follow all warnings and instructions on the device.
- Do not place this appliance on an unstable surface (such as a trolley, stand, table, etc.).
- If this appliance falls, it can cause serious damage.
- Do not use this appliance near water.
- Do not place this appliance near or above a radiator.
- The housing is equipped with openings for heat dissipation and ventilation. To prevent overheating during operation, the ventilation openings must not be blocked or covered.
- Do not place the appliance on a soft surface (e.g. bed, sofa, blanket, etc.). This will block the ventilation.
- The appliance must not be installed in a closed environment if adequate ventilation is not guaranteed.
- Do not spray any liquids onto the appliance.
- Disconnect the mains plug before cleaning. Do not use any liquid or foam cleaners.
- Clean the appliance with a damp cloth.
- Connect the device according to the power supply on the rating plate.
- This device is designed for the IT distribution system with 100 V - 230 V voltage.
- To prevent damage to the appliance, it is important that all appliances are properly earthed.
- Do not place any objects on the power cable and lay it in such a way as to avoid tripping hazards.
- If an extension cable is used for the appliance, make sure that the total capacity of all products using the cable does not exceed the current load.
- Ensure that the total current of all products connected to the socket does not exceed 15 A.
- Use a surge protector, a regulator or an uninterruptible power supply (UPS) to protect your system from sudden, temporary and reduced power.
- Secure the system cable and mains cable properly and ensure that no objects are pressing on the cable.
- Do not insert any objects into the appliance through the openings in the housing. There is a risk of a short circuit, which can lead to fire or electric shock.
- Do not attempt to repair the appliance yourself. Always contact an authorized customer service centre.
- If any of the following conditions occur, unplug the appliance and send it to an authorized service centre for repair
  - The mains cable or plug is damaged or worn;
  - Liquid has penetrated the appliance;
  - The device has been exposed to rain or water;
  - The device has been dropped or the housing has been damaged;
  - The function of the device has obviously changed;
- The appliance cannot be operated as described in the operating instructions.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)