

DIGITUS® DisplayPort Connection Cable, 2m

AK-340106-020-S
EAN 4016032450313



DisplayPort Connection Cable, Type DP M/M, 2.0m,w/lock, UHD 8K 60Hz, DP 1.4, bl

With this cable standard, this DisplayPort cable supports all of today's requirements - from the playback of high-resolution UHD 8K content through 8-channel audio transmission to the support of HDCP and DPCP encryptions. Mirror your laptop desktop on a large monitor or extend your desktop with another DisplayPort display. This high-quality cable allows rapid data transfer without jerking, even in demanding graphics applications or games. Gold-plated contacts and double shielding of the cable ensure maximum conductivity and trouble-free transmission.

Ideal for CAD/CAM, GIS, 3D modeling, real time simulation, and more.

- Transfer rate: up to 32.4 GBit/s
- Supports up to 8K@60Hz (Ultra HD) resolutions
- Supported video resolution: 7680 x 4320 dpi; 5120 x 2880 dpi; 3840 x 2160 dpi
- Color depth: 24bit RGB
- Supports 1-8 audio channels for audio transmission
- Audio sampling frequencies: 32-192 kHz with max. bit rate of 4,608 kB/s

- Supports HDCP and DPCP
- Plug & Play installation
- DisplayPort version: 1.4

Attributes

- AWG: 30
- Color cable: black
- Connector 1: DP, plug
- Connector 2: DP, plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.4
- Ferrite filter: none
- HDTV Standard: Ultra HD 8K
- Hoods: molded
- Interlock: Snap fastener
- Resolution max.: 7680 x 4320 Pixel, 60Hz
- Length: 2 m
- AOC - Active Optical Cable: no
- Shielding: single shielding

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|--------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 50 | 7.75 | 33.00 | 44.00 | 22.00 | 31.94 |
| Packaging Unit Inside | 1 | 0.13 | 28.00 | 36.00 | 25.00 | 25.20 |
| Packaging Unit Single | 1 | 0.16 | 3.00 | 17.00 | 25.00 | 1.28 |
| Net single without Packaging | 0 | 0.16 | 3.00 | 15.00 | 14.00 | 630.00 |

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com