**DIGITUS®**

DIGITUS CAT 6A U/UTP slim patch cord

DK-1617-A-150S
EAN 4016032461777

CAT 6A U-UTP slim patch cord, Cu, LSZH AWG 28/7, length 15 m, color grey

DIGITUS® slim patch cords are characterised by their small outer diameter and flexible sheath. Slim design enables versatile use in your network. Moreover, The DIGITUS® Category 6A Class EA patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6 A specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 6A cabling. The performance is tested up to 500 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 6A, because of the transparent yellow colored connector.

Enables flexible and space-saving cabling in your network

- 2x RJ45 (8P8C) connectors
- Boots with kink protection, strain relief and latch protection
- Length marking on boot
- Conductor: Copper (Cu)
- Bending radius: 4D (outer diameter x 4)
- outer diameter: 3,65 mm
- Configuration: 1:1
- Category: CAT 6A
- Shielding: U-UTP, unshielded
- Length: 15 m
- Color: grey
- Jacket: LSOH
- Slim Version: yes
- Structure: 4 x 2 AWG 28/7, twisted pair

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	30	8.00	32.00	50.00	21.00	33.60
Packaging Unit Inside	1	0.27	32.00	23.00	3.40	2,502.40
Packaging Unit Single	1	0.27	32.00	23.00	3.40	2,502.40
Net single without Packaging	0	0.24	21.00	21.00	3.40	1,499.40

More images:

DK-1617-A-150S // CAT 6ₐ U/UTP Slim Patch Cord

Router
Switch
Wall Outlet
Floor tank

Computer
Server