

DIGITUS Combination wall-mounted housing 254 mm (10") and 482.6 (19") mm

DN-1019

EAN 4016032462811



10" and 19" combi wall mounting cabinet 10U horizontal (10"), 5U vertical (19"), grey

With a round profile frame installed at the front, the wall-mounted enclosure offers the option of horizontal mounting of 254 mm (10") components (10 height units) and, alternatively, vertical mounting of 482.6 mm (19") components (5 height units). The front profile frame is depth-adjustable. There is also a profile hole integrated into the rear section of the enclosure frame for mounting additional components with 254 mm (10") dimensions. The enclosure is made from a robust steel construction. The cable entry openings in the roof, base and rear provide the best options for tidy cable management. The compact enclosure is therefore ideal for all common IT and telecommunications applications, especially where space is limited and in private households.

DIGITUS® wall-mounted enclosures are manufactured, designed and developed to meet the high demands of IT infrastructure.

- Lockable safety glass door with 200° door opening angle
- 1-point locking on the front door
- Circular profile frame mounted on the front inside the enclosure, galvanized

- Maximum installation depth: approx. 260 mm to rear panel; approx. 220 mm to rear profile perforation
- 1.1 - 1.5 thick sheet steel with a high load-bearing capacity, powder-coated
- Pre-punched cable inlets in the roof, floor and rear side
- Ventilation slots for active and passive ventilation
- Load capacity of the profile rails: 30 kg

Attributes

- Cabinet type: Wall mounting cabinet
- Color: light grey, RAL 7035
- Depth: 350 mm
- Front door: Glass door, single opening
- Load capacity: 30 kg
- Side panels: Both sides
- Units: 10
- Width: 350 mm
- IP protection class: IP20
- Mounted: yes

Package contents

- Installation set (screws, cage nuts, washers)
- 2 x key

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	11.50	35.50	35.50	56.00	70.57
Packaging Unit Inside	1	11.50	35.50	35.50	56.00	70.57
Packaging Unit Single	1	11.50	35.50	35.50	56.00	70.57
Net single without Packaging	0	10.30	35.00	35.00	55.00	67.38

More images:



Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com